

## COMPRESSED AIR QUATTRO TANDEM



Quattro Tandem

Optionally with 1 or 2 aggregates each 4 cylinders, oil-free

frequency	50 / 60 Hz
output at 5 bar with 1 aggregate*	220 / 255 l/min
output at 5 bar with 2 aggregates*	440 / 515 l/min
tank capacity	90 l
pressure range	5,5 - 7,5 bar
noise level with 1 aggregate**	69 / 70 dBA
noise level with 2 aggregates**	72 / 73 dBA

(Further technical data for all available compressors can be found at the end of the chapter)

Order number	Product description	Price/unit €
4642-54	<b>Quattro Tandem Compressor with Membrane Drying Unit</b> and electronic control (network compatible) voltage 400 V (3~) net weight 120 kg dimensions (HxWxD) 82 x 102 x 62 cm	6.700,00
4682-54	<b>Quattro Tandem Compressor with 2 Membrane Drying Units and 2 Aggregates</b> and electronic control (network compatible) voltage 400 V (3~) net weight 170 kg dimensions (HxWxD) 82 x 102 x 62 cm	9.900,00
4682-52	<b>Quattro Tandem Compressor with 2 Membrane Drying Units and 2 Aggregates</b> voltage 230 V (3~) net weight 170 kg dimensions (HxWxD) 82 x 102 x 62 cm	9.900,00
SERVW10003	<b>Warranty extension for Quattro Tandem to 5 years</b>	450,00
5450-980-60	<b>Fine Filter Set for a 4-cylinder compressor</b> contains all filters for the Aggregate and Membrane Drying Unit	210,00
5450-980-61	<b>Bacterial Filter Set for a 4-cylinder compressor</b> contains all filters for the Aggregate and Membrane Drying Unit, with Bacterial filter	340,00
6040-992-00	<b>Pressure Reducer</b> adjustable, for Quattro with quick connector for all Silver Airline and new Tornado Compressors, if needed you can order it as an extra part	140,00
4682600054	<b>Aggregate Retrofitting Set for Quattro Tandem</b> for converting Quattro Tandem 4642-51 into 4682-51 and 4642-54 to 4682-54; 50 / 60 Hz; comprises: 1 x Compressor Aggregate and 1 x Membrane Drying Unit	4.690,00

\*Output measured without Membrane Drying Unit

\*\* Average value at 5 bar without Membrane Drying Unit



## SUCTION ACCESSORIES



Spittoon Bowl Valve



Place Selection Valve



Order number	Product description	Price/unit €	
7560700052	<b>Spittoon Bowl Valve 24 V ~/=</b> for installing into treatment unit without touch-key module, without connections*	490,00	
7560700051	<b>Spittoon Bowl Valve 24 V ~/=</b> for installing into treatment unit with touch-key module for cleaning function, without connections*	630,00	
7560700064	<b>Spittoon Bowl Valve 24 V ~/=</b> for installing into floor connection box into treatment unit, without touch-key module, without connections*	572,00	
7560-570-53	<b>Spittoon Bowl Valve for installation into A-dec Radius and Performer</b> in floor connection box incl. fittings and Place Selection Valve	825,00	
7560-570-54	<b>Spittoon Bowl Valve for installation into A-dec 500, 461 and 561</b> incl. Place Selection Valve and fittings. For A-dec 461 the relay box 7560-565-50 is required	763,00	
7560-570-55	<b>Spittoon Bowl Valve for installation into A-dec 300</b> incl. Place Selection Valve and fittings	850,00	
7560-570-62	<b>Spittoon Bowl Valve for installation into A-dec 200</b> incl. Place Selection Valve and fittings	990,00	
7560-500-60	<b>Place Selection Valve 24 V=/~</b> note: when fitting dry or wet suction systems with DürrConnect parts take into consideration the possibility of using the DürrConnect Installation Set 0700-700-50	123,00	

\* use parts as required from DürrConnect installation case

Suction

## SUCTION CENTRAL-SUCTION SYSTEMS DRY SUCTION



V 900 S

### We recommend: Orotol® Basic-Set

A complete package to ensure the longevity of the Suction Unit with optimal disinfection and cleaning

Order number	Product description	Price/unit €	
7131-01/002	<b>V 900 S Central Suction Machine</b> up to 5 treatment positions, with 3 operators working simultaneously 230 V 1~, 50 Hz, with condensate separator and control unit 230 V 1~ / 24 V~	3.020,00	
7131-02/002	<b>V 900 S Central Suction Machine</b> up to 5 treatment positions, with 3 operators working simultaneously 400 V 3~, 50 Hz, with condensate separator and control unit 400 V 3~ / 24 V~	3.020,00	
7136-02/002	<b>V 1200 S Central Suction Machine</b> up to 6 treatment positions, with 4 operators working simultaneously 400 V 3~, 50 Hz, with condensate separator and control unit 400 V 3~ / 24 V~	3.350,00	
7136-02/003	<b>V 1200 S Central Suction Machine</b> up to 6 treatment positions, with 4 operators working simultaneously 230 V 3~, 50 Hz, with condensate separator and control unit 230 V 3~ / 24 V~	3.350,00	
SERVW11003	<b>Warranty extension for V 900/1200 S to 5 years</b>	185,00	
7137-02	<b>V 2400 Central Suction Machine</b> up to 12 treatment positions, with 8 operators working simultaneously 400 V 3~, 50 / 60 Hz, with condensate separator and control unit 400 V 3~ / 24 V~	5.600,00	
SERVW11002	<b>Warranty extension for V 2400 to 5 years</b>	340,00	
CDS110P9950	<b>Orotol® Basic-Set</b> for the user friendly disinfection and cleaning of dental suction systems. Pack size: 1 x 2,5 litre bottle Orotol® plus, 1 x 2,5 litre bottle MD 555 cleaner, 1 x 750 ml bottle MD 550, 1 x OroCup	106,50	

Suction