

ROTARY MOWER

WITH BIOCLIP OPTION



VITRA

ROTARY MOWER



Mounted with 3 knives
Each knife with 2 blades



Large cutting width
Available from 1300 to 1800 mm



Quick Mounting
Standard A-frame

VITRA

A strong Danish family..

ROTARY MOWER



Perfect and professional result!

The rotary mower is a professional cutter, installed with three knives which overlap each other to ensure an optimal and beautiful mowing result. The mower is installed in the front, with the large discharge width which ensures that the cut-off grass is evenly distributed throughout the area, even in wet or high grass. Optionally the mower can be installed with bioclip. After use the mower can be tilted upwards, so the knives and mowing deck easily can be cleaned and maintained. The mower is installed in a floating frame, and can additionally be delivered with hydraulic height adjustment and hydraulic tipping of the mowing deck, which ensures even faster and easier maintenance and cleaning.

- Standard A-frame mounting
- Optional with hydraulic tipping
- Three knives
- Floating frame mounting
- 4 pcs. 3" rubber support wheel
- Specifically designed for Vitra



The mower can be tilted upwards, to ensure easy cleaning and maintenance. Additionally hydraulic tipping is possible.



Additionally the cutting height can be hydraulically adjusted, which can easily be done by the driver directly from the cabin.



The mower is installed with strong rubber-support wheels in the front and back to ensure optimal stability.

Manufacturer:

Lindholdt Maskiner A/S
Industrivej 8
DK-6818 Arre

Tlf: +45 76 77 44 77
Mail: Info@lindholdt-maskiner.dk
Web: www.lindholdt-maskiner.dk



The rotary mover is specifically adjusted to fit Vitra, so the strength of the machine can be fully exploited with a perfect result as a consequence.

RED3108 / 3112 (Vitra 2030/2037)

| | |
|------------------------|---------------------------------------|
| Width: | 1450 / 1670 mm. |
| Cutting width: | 1300 / 1500 mm. |
| Cutting height: | 25-110 mm. |
| Net weight: | 250 / 265 Kg. |
| Performance: | 1300 mm: 3600-10400 m ² /h |
| | 1500 mm: 4500-12000 m ² /h |

RED3115 (Vitra 2045/2050/2067)

| | |
|------------------------|---------------------------------------|
| Width: | 1930 mm. |
| Cutting width: | 1800 mm. |
| Cutting height: | 25-110 mm. |
| Net weight: | 290 Kg. |
| Performance: | 1800 mm: 5400-14500 m ² /h |

The rotary cutter is available in both a TH series and in a FR series, where cutting height and tilt off cutting board takes place hydraulically.

For additional data, please see the price list.

Vitra is sold through a strong, network of dealers and service centres. All with specially trained staff, which is connected directly to Vitra's intern network.

Dealers and service centres are spread throughout the country, which means that there is always a service partner near you ready to advise you and your Vitra.

Your local Vitra dealer:

According to the preliminary purchase contract No VSA20211215/1, in accordance with point 3.6 of the contract.
15-12-2021, Holland Sadcc Trading Company B.V.

See distributors and additional information on: www.lindholdtmaskiner.dk