

Gaminio duomenų lentelė

Specifikacijos



Switch disconnecter, MasterPact NT12HA, 1250A, 75kA/440VAC 50/60Hz (Icm), 4 poles, fixed

47166

Main

Range	MasterPacT
Product name	MasterPact NT
Product or component type	Switch disconnecter
Device short name	MasterPact NT12
Switch-disconnector name	MasterPact NT12HA
Device application	Protection
Poles description	4P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	1250 A AC 50/60 Hz 690 V
[Ui] rated insulation voltage	1000 V AC 50/60 Hz IEC 60947-3
[Uimp] rated impulse withstand voltage	12 kVIEC 60947-3
[Icm] rated short-circuit making capacity	75 kA 220...690 V AC 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz IEC 60947-3
Breaking capacity code	HA
Suitability for isolation	Yes IEC 60947-3
Contact position indicator	Yes
Visible break	No
Pollution degree	3 IEC 60664-1

Complementary

Control type	Push-button
Mounting mode	Fixed
Upside connection	Front
Downside connection	Front
Operating rate	10 cyc/h maximum
[Icw] rated short-time withstand current	36 kA 0.5 s IEC 60947-3 36 kA 1 s IEC 60947-3 20 kA 3 s IEC 60947-3

Mechanical durability	12500 cycles without maintenance IEC 60947-3
Electrical durability	AC-23A 3000 cycles 690 V AC 50/60 Hz without maintenance IEC 60947-3 AC-23A 6000 cycles 440 V AC 50/60 Hz without maintenance IEC 60947-3 AC-3 6000 cycles 440 V AC 50/60 Hz without maintenance IEC 60947-3
Connection pitch	70 mm
Height	301 mm
Width	346 mm
Depth	196 mm
Net weight	18 kg

Environment

Standards	IEC 60947-3
Product certifications	LCIE ASEFA
Ambient air temperature for operation	-5...70 °C
Ambient air temperature for storage	-40...85 °C

Pakavimo vienetai

Pirmos pakuotės vieneto tipas	PCE
Vienetų skaičius 1 pakuotėje	1
1-os pakuotės aukštis	41,0 cm
1-os pakuotės plotis	39,0 cm
1-os pakuotės ilgis	30,0 cm
1-os pakuotės svoris	19,242 kg

Offer Sustainability

Tvaraus pasiūlymo statusas	„Green Premium“ gaminys
REACH direktyva	REACH deklaracija
ES RoHS direktyva	Atitinka ES RoHS deklaracija
Be gyvsidabrio	Taip
Kinijos RoHS direktyva	Kinijos RoHS deklaracija Produktas neįeina į Kinijos RoHS apimtį. Medžiagų deklaracija pateikiama jūsų informacijai.
RoHS išimčių informacija	Taip
Aplinkosauginės informacijos atskleidimas	Produkto aplinkosaugos profilis
Žiedinės ekonomikos profilis	Eksploatavimo ciklo pabaigos informacija
Be PVC	Taip

Contractual warranty

Garantija	18 months
-----------	-----------

Rekomenduojamas (-i) pakeitimas (-ai)