



VU36NE

**Encl.,Volta,flush,3x12MOD,IP30,Version NCEE**

## Technical properties

### Architecture

Fixing mode	flush-mounting
-------------	----------------

### Functions

With a pipe-in lead	Yes
---------------------	-----

### Configuration

Number of modules	36
-------------------	----

### Main electrical features

Nominal voltage	400 V
-----------------	-------

### Electric current

Rated current	63 A
---------------	------

### Dimensions

Insertion depth	89 mm
Depth of installed product	98 mm
Internal depth	91.5 mm
Height of installed product	630.5 mm
Installation height	595 mm
Length	630.5 mm
Width of installed product	348 mm
Width in division units	12
Thickness of sidewall material	2.5 mm
Built-in height	615 mm
Built-in width	314.5 mm

### Cover, door

Type of door closing	Latch
Identification of protection index	30
Interlockable	No
Number of keylock of the door	0
Cover type	With Notch
Door locking	without
Door leave	single
Cover type	Door
Transparent cover or door	No

### Materials

Colour	pure white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	plastic
Type of surface treatment	untreated
<b>Installation, mounting</b>	
Suitable for outdoor use	No
<b>Settings</b>	
Enclosure type	Distributor empty cabinet
<b>Scope of delivery</b>	
With cover	No
<b>Equipment</b>	
Number of units	12
Number of rows	3
Quantity of rails	3
Can be accessorized	Yes
Number of openings for flange plates	0
Extension possible	Yes
Earthing terminal block	Yes
Neutral terminal block	No
Signal passing door	No
<b>Standards</b>	
GWT Glow wire test	650 °C
European directive WEEE	concerned
Protection class according to IEC-61140	II
<b>Safety</b>	
IK protection code against mechanical impacts	IK07
Protection index IP	IP30
Protection class	isol.class II
Halogen free	Yes
Impact strength	IK05
<b>Use conditions</b>	
Operating temperature	-40...40 °C
<b>Identification</b>	
Search words	Volta distribution board;distributor;distribution board;flush-mounted;sheet metal door