












FA 30 200 15

P. 1 | 2



HS CODE
56090090
DĚŽUTĚS DYDIS / Vnt
60 x 40 x 24 / 10
AET N°2777/10361-02/E05-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16023-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom



REF.	FA 30 200 15
LG.  KG	1.5 m (kartu su karabinu) ----- Max. 100 KG
CE	EN 355:2002
MAT.	 PA 12 mm
	45 mm
	 FA 50 101 17 / FA 50 207 55
	NE
+	PPE-R 11.063
	1.80 KG



Largeur de l'absorbeur d'énergie
Amortizatoriaus plotis
Ancho del absorbedor de energía
Larghezza del assorbitore di energia
Breite des Falldämpfers

LG.



Longueur Poids maxi utilisateur
Ilgis Maks. vartotojo svoris
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas
Karabinų medžiaga
Material conector alto / conector bajo
Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Ouverture
Atidarymo dydis
Apertura
Apertura Öffnung



Homologué pour le travail à proximité d'arêtes vives
Patvirtintas darbui šalia aštrių kraštų
Homologado para trabajo cerca de aristas vivas
Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten

KOPIJA TIKRA