

技术要求:

- 1.未特殊说明, 铝材平光本色阳极氧化, 膜厚 $\geq 10\mu\text{m}$;
- 2.硬度要求: HW12~16;
- 3.表面无划伤、无划痕, 边缘无锐边、尖角、毛刺等;
- 4.未注公差按(GB/T 1804-2000)公差等级m级(中等级);
- 5.未注圆角为R0.5~1.0;
- 6.重量为0.718kg/m。

Hopergy 厦门华谱光电科技有限公司
 XIAMEN HOPERGY PHOTOVOLTAIC TECHNOLOGY CO.,LTD.

标记 Mark	处数 Qty	更改内容 Updated Content	签字 Sign	日期 Date	版本 Version A/0	视角 View A4	设计 Design	材料 Material AL6005-T5	产品名称 Part Name MSR30导轨
					比例 Scale 共 1 张, 第 1 张		审核 Review	重量 Weight 0.273kg	
							批准 Approve	编号 Part No.	图号 Dwg No. HOP-HP102039-01

NOVA METAL ROOF SOLUTION MINI RAIL

PRODUCT SHEET

NOVA SERIES PRODUCTS

The NOVA Mini Rail Mounting System is a PENETRATIVE TIN ROOF system, designed and engineered with its focus on reducing installation times by eliminating the need of traditional full length rail support, making it QUICK & SIMPLE.

The system can be used with any PV panel dimensions and be installed in any orientation.



FAST & EASY
INSTALLATION



COST EFFECTIVE
SOLUTIONS



QUALITY
ASSURED




15 YEAR
WARRANTY




KEY FEATURES




1 The unique structural design ensures maximum strength and support required for PV mounting.




2 Direct attachment onto the metal roof.




3 Each MINI Rail includes a EPDM rubber base pad that cushions the system against the mounting surface and provides waterproofing.



4 Panel clamps feature a clip in mechanism for easy installation onto the MINI rail.



5 The NOVA panel clamps incorporates a user-friendly Clip-in design and integrated earthing pins, eliminating the requirement for an additional grounding plate.



6 Simplest flush mount solution on the market.