

Radifocus® Guidewire M Shapeable - Guidewire

- Characteristics
- General Specifications
- Item Specifications



Radifocus® Guide wire M Shapeable type are Nitinol hydrophilic guide wires covered with polyurethane and hydrophilic coating with high torque control and shapeable tip for special sites particularly difficult to reach.

Indicated for use for angiography in Coronary and Peripheral territories, catheterization, embolization, and peripheral stenting in difficult to access, small, spasmatic and acute angled vessels.

Characteristics

- Tapered-preformable tip to reach difficult access sites.
- Super elastic Nitinol core: excellent shape memory, greater flexibility and increased control in difficult cases. Prevents kinking for an easier and faster catheter placement.
- Polyurethane radiopaque jacket: smooth surface to minimize blood adhesion to the wire, allow soft and atraumatic navigation and higher visibility (tungsten).
- Extra flexible and non traumatic tapered tip: increased guide wire flexibility for a smooth and safe navigation through vessels.
- Extra hydrophilic ("M" polymer coating): smooth navigation (no friction) through catheter and vessels, time savings to user. Prevents blood platelet adhesion and thrombus formation.
- One-piece construction: improved wire control through the vessel, true one-to-one torque transmission, thus providing an easier, faster and safer navigation through catheter and vessels.
- Rounded end: decreased likelihood of vessel trauma and smoother wire insertion.

General Specifications

Core material	Nitinol with tapered pre-formable tip
Radiopaque jacket	Polyurethane layer containing tungsten
Hydrophilic coating	"M" polymer
Guide wire diameter	0.035" (0.89 mm)
Guide wire lengths	150 cm / 180 cm
Distal flexible length	30 mm
Distal curves	Straight / 45° angled
Units per box	5

Item Specifications

Outer diameter	Length	Flexible length	Distal curve	Item reference
0.035" / 0.89 mm	150 cm	30 mm	Straight	RE*GL35153M
0.035" / 0.89 mm	150 cm	30 mm	Angled	RE*GK35153M
0.035" / 0.89 mm	180 cm	30 mm	Straight	RE*GL35183M
0.035" / 0.89 mm	180 cm	30 mm	Angled	RE*GK35183M

Please quote above item reference codes when placing an order.