

54 pinkino dolls

Radifocus® Guide wire M

Standard type (For catheter exchange)

Guide wires



Length > 220 cm

Nitinol hydrophilic guide wires covered with polyurethane and hydrophilic coating for an absolute maneuverability and absence of friction.

- Extra flexible and non traumatic tapered tip
- Extra hydrophilic thanks to the exclusive "M" polymer coating
- Super elastic alloy core in Nitinol
- One-piece construction for a better push and torque transmission

Specifications

RF-GA18223M	0.018" / 0.46 mm	220 cm	30 mm	Angled
RF-GA18263M	0.018" / 0.46 mm	260 cm	30 mm	Angled
RF-GS18263M	0.018" / 0.46 mm	260 cm	30 mm	Straight
RF-GS25263M	0.025" / 0.64 mm	260 cm	30 mm	Straight
RF-GA25263M	0.025" / 0.64 mm	260 cm	30 mm	Angled
RF-GS32263M	0.032" / 0.81 mm	260 cm	30 mm	Straight
RF-GA32263M	0.032" / 0.81 mm	260 cm	30 mm	Angled
RF-GS35223M	0.035" / 0.89 mm	220 cm	30 mm	Straight
RF-GA35223M	0.035" / 0.89 mm	220 cm	30 mm	Angled
RF-GS35261M	0.035" / 0.89 mm	260 cm	10 mm	Straight
RF-GS35263M	0.035" / 0.89 mm	260 cm	30 mm	Straight
RF-GA35261M	0.035" / 0.89 mm	260 cm	10 mm	Angled
RF-GA35263M	0.035" / 0.89 mm	260 cm	30 mm	Angled
RF-GA35303M	0.035" / 0.89 mm	300 cm	30 mm	Angled
RF-GA38223M	0.038" / 0.97 mm	220 cm	30 mm	Angled
RF-GS38263M	0.038" / 0.97 mm	260 cm	30 mm	Straight
RF-GA38263M	0.038" / 0.97 mm	260 cm	30 mm	Angled

Other code numbers are available on special demand. For any further information, please contact your Terumo local representative.

Units per box: 5