



[Skip to main content](#)

Macro Lens

# Canon RF 100mm F2.8L Macro IS USM

## Specifications

### Specifications

- **1.4x Macro magnification<sup>1</sup>**

Revealing hidden detail

- **Spherical Aberration Control**

For the ultimate control over bokeh and soft focus

- **F2.8**

For great performance in all situations

- **Dual Nano USM**

For smooth, fast and near silent focusing

- **Up to 5-stops<sup>2</sup> optical Hybrid Image Stabilizer**

Exceptional stability in low light levels

- **Lens Control Ring**

Change settings while still viewing the subject

## Specifications in detail

### Optical Features / Specifications

- Image Size  
Full Frame
- 35mm Film Equivalent Focal Length (mm)  
100
- Angle of View (Horizontal, vertical, diagonal)  
20°, 14°, 24°
- Lens Construction (Elements/Groups)  
17 / 13
- Number of Diaphragm Blades  
9
- Minimum Aperture  
32
- Closest Focusing Distance (m)  
0.26
- Maximum Magnification (x)  
1.4
- Distance Information  
Yes
- Image Stabilizer OIS<sup>1</sup>  
5-stops<sup>2</sup> (2-stops at 1.0x magnification, under Canon test standards)
- Image Stabilizer IBIS x OIS<sup>3</sup>  
8-stops<sup>4</sup>
- AF Actuator  
Dual Nano USM

## Accessories

- Lens Cap  
E-67 II
- Lens Hood  
ET-73C
- Lens Case/Pouch  
LP1222
- Rear End Cap  
Lens Dust Cap RF
- Magnification with Extension Tube EF12 II

Not Compatible

- Magnification with Extension Tube EF25 II

Not Compatible

- Extender Compatibility

Not Compatible

- Other Accessories

Macrolite Adapter 67 (optional),

Tripod mount ring E (B) with adapter (optional)

## Physical Specifications

- Dust/Moisture Resistance

Yes<sup>5</sup>

- Filter Diameter (mm)

67

- Max. Diameter x Length (mm)<sup>6</sup>

81.5 x 148

- Weight (g)

685

Although the lens features dust- and water-resistant construction, this cannot completely prevent dust or water droplets from entering the lens.

1. Tested under CIPA standards

2. Tested under CIPA standards

3. Tested under CIPA standards


4. Tested under CIPA standards

5. Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

6. Lens dimensions when in retracted state

# Canon

## Have your say:



Please complete a **1 minute survey** to help us improve our support website experience

[Complete The Survey.](#)

No, Thank You