

Recommendation



XPROIIL

[Learn More](#)



XPROIIL

[Learn More](#)

Tech Specs

Model	XPROIIC	XPROIIN	XPROIIS	XPROIIF	XPROIIO
Compatible cameras	Canon EOS cameras (E-TTL II autoflash) Support for the cameras that have PC sync socket	Nikon cameras (i-TTL autoflash) Support for the cameras that have PC sync socket	Sony cameras (TTL autoflash) Support for the cameras that have PC sync socket	Fujifilm Cameras (Autoflash) Support for the cameras that have PC sync socket)	Olympus Panasonic Cameras (TTL autoflash) Support for the cameras that have PC sync socket
Power supply	2*AA batteries				
Flash Exposure Control					
TTL autoflash	√				
Manual flash	√				
Stroboscopic flash	√				
Functions					
High-speed sync	√ (FUJIFILM set on cameras)				

XPRO II C/N/S/F/O

Specs

In the Box

Downloads

Recommendation

Flash exposure compensation $\pm 3\text{EV}$ (exposure value), adjustable in 1/3 EV increment

Flash exposure lock \checkmark

Focus assist \checkmark

Modeling lamp flash Control the modeling lamp flash by flash trigger

Beeper Control the Beeper by flash trigger

Wireless Shutter The receiver end can control the camera shooting through the 2.5mm sync cord jack

Zoom setting Adjust the ZOOM value by the transmitter from AUTO or 24 to 200

TCM function Transform the TTL shooting value into the output value in the M mode

Firmware upgrade Upgrade through the Type-c USB port

Memory function Settings will be stored 2 seconds after last operation and recover after a restart

Display Large LCD panel, backlighting ON or OFF

Wireless Flash

Transmission range (approx.) 0-100m

Built-in wireless 2.4GHz

Modulation mode MSK

Channel 32

Wireless ID OFF, 01-99

Group 5 or 16 (selectable in the menu)

Other

Dimension 95mm*62mm*49mm

Net Weight 93g

Downloads

