

## MX-T6-Pro

### LCD Digital Tube Roller

## Features

- LCD displays the speed and time
- Rocking & rolling at variable-speed
- Adjustable speed range from 10 to 70 rpm
- Six roller design for gentle and efficient rolling, and easy to clean
- DC brushless motor quiet and maintenance free
- Cold room and incubator compatible



LCD display



Timer

8. Galimybė skaitiškai nustatyti apsisukimo greitį  
3. paskirtis



## MX-T6-S/S+

### Standard tube roller

## Features

- Adjustable speed range from 0 to 70 rpm
- Six roller design for gentle and efficient rolling, and is easy to clean

## Applications

DLAB laboratory tube rollers provide a gentle and highly efficient rolling motions, deal for mixing blood samples, viscous substances and liquid-solid suspensions. Used in a variety of applications, such as the prevention of blood coagulation, immune precipitation, etc.

| Specifications                               | MX-T6-Pro           | MX-T6-S                          | MX-T6-S+           |
|--|---------------------|----------------------------------|--------------------|
| Amplitude                                    | 24mm                | 7. rotacijos amplitudė           |                    |
| Motor type                                   | Brushless DC motor  | Brush DC motor                   | Brushless DC motor |
| Rocking motion                               | Rocking and rolling | Rocking and rolling              |                    |
| Max. load capacity                           | 4kg                 | 4kg                              |                    |
| Number of rollers                            | 6                   | 4. volelių skaičius              |                    |
| Roller size[length]                          | 280mm               | 280mm                            |                    |
| Speed range                                  | 10 - 70rpm          | 6. apsisukimo greičio intervalas |                    |
| Speed display                                | LCD                 | Scale                            |                    |
| Timer  | Yes                 | 9. laikmatis                     |                    |
| Timer display                                | LCD                 | -                                |                    |
| Time setting range                           | 1-1199min           | -                                |                    |
| Operation mode                               | Continuous/timer    | Continuous                       |                    |
| Voltage,Frequency                            | 100-240V,50/60Hz    | 100-240V,50/60Hz                 |                    |
| Power  | 30W                 | 25W                              |                    |
| Dimension [D×W×H]                            | 485×250×100mm       | 485×250×100mm                    |                    |
| Weight                                       | 5.1kg               | 4.5kg                            |                    |
| Permissible ambient temperature and humidity | 5-40°C,80%RH        | 5-40°C,80%RH                     |                    |
| Protection class                             | IP21                | IP21                             |                    |