

Get up to 15% off with your business account, plus exclusive offers [Register your ABN now!](#)

## 46" VMB-U Ultra Narrow Bezel Video Wall

[Contact us](#)

[Features](#) [Spec](#) [Support](#) [Compare](#)



### 46" VMB-U Ultra Narrow Bezel Video Wall



LH46VMBUBGBXXY

- Transform any space with high impact visuals
- View content from any angle
- Vibrant images in any light

#### Choose size

46"

55"

46" VMB-U Ultra Narrow Bezel Video Wall  
46"

[Contact us](#)

# Always-on, space-saving solution with ultra-narrow bezels

Experience an immersive and dependable viewing experience, 24/7 with Samsung’s VMB-U series. The display’s slim depth and 500 nit brightness helps to ensure visible images and legible messages in a wide range of locations - from shopping malls to lobbies, meeting rooms, control rooms and more.



# Impactful Visuals

## Ultra-narrow bezels

With an ultra-narrow bezel measuring just 3.5mm, the UNB Video Wall delivers an impactful visual experience. Combined with a slender design and 69.9mm cabinet depth, you can create an immersive, captivating and dependable viewing experience.

# View content from a variety of angles

## Wide viewing angles

The display's wide viewing angles mean content is visible to viewers, even when not standing directly in front of the display. This helps to deliver clear information to audiences, in a range of layouts and locations.

# Vibrant images

## Non-glare panels

Non-glare panels are designed to improve visibility by minimising glare - helping to deliver clear messaging. Combined with a high contrast ratio and 24/7 operation, the display's non-glare panels help to provide good visibility in a variety of light conditions.



Image for illustrative purposes only

# Image enhancement

## Picture enhancer mode

Samsung’s powerful picture enhancement technology is designed to deliver vibrant and clear content. Picture Enhancer mode improves colour saturation and contrast by adjusting the gamma curve. Using Black Equaliser mode, dark images are lightened, illuminating details – helping to make information easier to see.

# Convenient mobile calibration

## Colour Expert Pro Mobile solution

Multi-step factory tuning provides uniform brightness and colour. Users can also fine-tune advanced settings with free powerful Colour Expert Pro software. For quick and simple calibration, Colour Expert Pro Mobile enables white balance adjustments for displays up to 5x5 using a mobile camera.

Mobile is required. Compatible with Samsung Galaxy S8, Samsung Galaxy Note 8, Samsung Galaxy S9 and later models.

# Display UHD content

## Daisy Chain and Optional Signage Player Box

Samsung video walls provide an impressive 4K UHD viewing experience with minimal effort. With daisy chain design utilising DisplayPort 1.2 and HDMI ports, when four compatible units are combined, the display can project UHD content across multiple screens. Display up to 5 x 5 — without requiring an external graphic card or UHD splitters. Samsung's UHD Signage Player Box streamlines functionality by combining the media player and content management software.

Four compatible screens (sold individually) are required to be connected to create UHD display.  
The Signage Player Box is sold separately.

# Durable and user-friendly design

## IP5X Verified

IP5x certified, the VMB-U series is dust-resistant and able to withstand a range of environmental conditions without needing to prepare additional enclosure in dusty places. An embedded, centrally located infrared receiver (IR) allows for flexible user control to the display.



# Specifications

## Display

**Diagonal Size**  
46"

**Resolution**  
1,920 x 1,080

**Brightness (Typ)**  
MAX 500 nit

**Viewing Angle (H/V)**  
178/178

**Color Gamut**  
72 %

**H-Scanning Frequency**  
62.7~72.3kHz

**V-Scanning Frequency**  
57~63Hz

**Operation Time Support**  
24/7

**Panel Type**  
IPS

**Pixel Pitch (HxV)**  
0.53x0.53

**Contrast Ratio<sup>5</sup>**  
1,200:1

**Response Time**  
8ms

**Glass Haze**  
25 %

**Maximum Pixel Frequency**  
82MHz

**Contrast Ratio (Dynamic)**  
45,000:1

## Connectivity

**HDMI In**  
2

**DVI In**  
Yes

**Version of DP**  
1.2

**USB**  
1

**Audio In**  
Yes

**Video Out**  
Yes

**RS232 In**  
Yes

**RJ45 In**  
Yes

**DP In**  
1

**Version of HDMI**  
2

**Version of HDCP**  
2.2

**IR In**  
Yes

**Audio Out**  
Stereo Mini Jack

**Power Out**  
No

**RS232 Out**  
Stereo Mini Jack

## Power

**Power Supply**  
AC100-240V 50/60Hz

**Power Consumption (Sleep Mode)**  
0.5 W

**Power Consumption (On Mode)**  
160 W

## Dimension

**Set Dimension (WxHxD)**  
1022 x 577 x 69.9 mm

**Package Dimension (HxWxD)**  
1193 x 719 x 257 mm

Shop

EXCLUSIVE APP OFFER

×

Weight

Net Weight  
15.7 kg

Package Weight  
22.2 kg

Operation Conditions

Temperature  
0°C~ 40°C

Humidity  
10 ~ 90%

Mechanical Specification

VESA Mount  
600 x 400 mm

Frame Material  
Glossy

Bezel Width  
2.25mm(U/L), 1.25mm(R/B)

Optional Feature

Mount  
Yes

Stand  
No

Certification and Compliance

EMC  
FCC (USA) Part 15, Subpart B Class ACE (Europe) :  
EN55032 : 2012 or 2015    EN55024:2010 or EN  
55035:2017VCCI (Japan) : VCCI CISPR32:2016 Class  
BKCC/EK (Korea) : Tuner : KN13 / KN20Tunerless : KN22  
/ KN24BSMI (Taiwan) : CNS13438 ( ITE EMI ) Class A /  
CNS14336-1 ( ITE Safety ) / CNS15663 (RoHS)C-Tick  
(Australia) : AS/NZS CISPR32:2015CCC(China)  
:GB/T9254-2008, GB17625.1-2012GOST(Russia/CIS) :  
ROCT CISPR 24-2013/ROCT CISPR 22:2005

Safety  
CB (Europe) : IEC60950-1/EN60950-1CCC (China) :  
GB4943.1-2011PSB (Singapore ) : PSB+IEC60950-1NOM  
(Mexico ) : Tunerless : NOM-019-SCFI-1998IRAM  
(Argentina ) : IRAM+IEC60950-1SASO (Saudi Arabia ) :  
SASO+IEC60950-1BIS(India) : IEC60950-1 /  
IS13252KC(Korea) : K 60950-1EAC(Russia) :  
EAC+IEC60950-1INMETRO(Brazil) :  
INMETRO+IEC60950-1BSMI(Taiwan) : BSMI+IEC60950-  
1RCM(Australia) : IEC60950-1/AS/NZS 60950-1UL(USA)  
: cUL60950-1 CSA (Canada) : cULTUV (Germany) :  
CENEMKO (Norway) : CE

Support

Find answers to your questions about the product

Product Support

[See More Content ↗](#)

User manual & Downloads

Quick Guide

ver 2205040 | 1.96 MB | May 13, 2022

MULTI LANGUAGE ⓘ

Download

User Manual

ver 2204180 | 11.54 MB | Apr 19, 2022


MULTI LANGUAGE ⓘ

Download

[See More Content ↗](#)

Compare the models

Compare with similar items



55" VMB-E Extreme Narrow Bezel Video Wall

LH55VMBEBGBXXY

55" VHB-E Extreme Narrow Bezel Video Wall

LH55VHBEBGBXXY

55" Full HD Videowall Display UD55E-B


LH55UDEBLBB/XY

55"

55"

55"

## Recently Viewed



Features and specifications are subject to change without prior notification. Images are used for illustrative purposes only.

### Subscribe

Company Name \*

Email Address \*

### Sales Enquiries

Get in touch with our sales team to discuss the best options for your business.

Request a call back

### Technical Support

Need support? Get in touch with our experts for product-specific support and technical assistance.

Request support

### Enterprise Customer ONLY

First Name \*

Last Name \*

Call 1800 91 92 93

☐ I acknowledge that my information will be processed in accordance with the [Samsung privacy policy](#).

\* Required

☐ We would like to receive marketing communications from Samsung and its partners.

Submit

Smartphones	Samsung Knox	Education	Why Samsung for Business	Environment
Tablets	Samsung DeX	Retail	Sign up	Security & Privacy
Enterprise Edition	Smart Display Solutions	Finance	Trade-up	Accessibility
Rugged	Smart LED Display Solutions	Government	Online Warranty	Diversity · Equity · Inclusion
PC	Commercial TVs Solutions	Corporate	Shop FAQ	Corporate Citizenship ↗
Smart Display	Monitor Solutions			Corporate Sustainability ↗
Smart LED Display	WindFree™	<b>Global Sites</b>		
Commercial TVs		Technology Partnership ↗		<b>About Us</b>
Business Monitors		Partner Programme ↗		Company Info
VRF		Display Solutions ↗		Business Area
Air Purifiers		LED ↗		Brand Identity
		Semiconductor ↗		Careers
		Healthcare Products ↗		Investor Relations ↗
		Networks ↗		Newsroom ↗
				Ethics
				Samsung Design ↗

Copyright© 1995–2024 SAMSUNG All Rights Reserved.

