

		not protruding above the bottom level. A rubber sealing gasket must be inside outlet openings. Diameter openings must be such that standard 50 mm (d50) diameter PVC pipe must slide into the water outlet opening. With the water level regulator in the water outlet opening.	
4.	Complete with:	Each individual trough must be complete with four incubation boxes for spawn incubation. The incubation boxes must be rectangular. The incubation box size must be so, that the lateral edge of the box should be placed on the edges of incubation trough and the side walls tightly fit against the inner surface side walls of incubation trough. The laterals and frontal walls of the box must be made of fiberglass plastic or an equivalent material, and the bottom and part of the rear wall must be made of perforated (hole diameter $2.0 \pm 0.1$ mm) stainless steel or equivalent material.	YES  YES  The laterals and frontal walls of the box must be made of glass reinforced polyester, and the bottom and part of the rear wall must be made of perforated (hole diameter 2.0 mm) stainless steel
5.	Other parameters	All Equipment must be brand new, not previously used and shall conform with the requirements prescribed by the relevant legal acts of the Republic of Lithuania and the EU (bearing CE marking and/or have the Declaration of Conformity (certificates))  Technical documentation of the manufacturer or other equivalent evidence (e.g. photos, drawings, etc.), proving that each requirement mentioned above is satisfied, shall be submitted together with the tender.	YES
<b>III. Incubation trough with seven incubation boxes</b>			
1.	Manufacturer	Shall be specified	„SDK“ Sp. z o.o.
2.	Model	Shall be specified	SDK Hg 7b
3.	Technical data	Made of fiberglass plastic or equivalent material, rectangles with rounded corners, with even and smooth inner surface.  Trough dimensions: outer length $400 \pm 5$ cm;	Made of glass reinforced polyester laminate, rectangles with rounded corners, with even and smooth inner surface.  400 cm