

E9X HIGH DEPENDENCY BED

# Enterprise 9000X



3PD 2.

3 PD 19.2.

## Designed for you and your patient

The Enterprise 9000X hospital bed from Arjo delivers significant benefits to the patient, caregiver and healthcare facility. The daily challenges faced by nursing teams on hospital wards have inspired Arjo to improve upon an established solution, trusted by hospitals around the globe. In the development of the Enterprise 9000X hospital bed, Arjo has focused on key customer needs common to all healthcare environments, namely:

- Safety for both patient and carer.
- Compliance with new international standards.
- Equipment that is robust, intuitive and easy to use.
- Solutions focused on the quality of care for patients.

The Enterprise 9000X bed for intensive care and high dependency patients, is based on the key features of the Enterprise 5000X and 8000X hospital beds, with additional focus on patient safety and clinical functionality. With its patented profiling system, integrated weighing scale, bed exit alarm and under-bed anti-entrapment sensors, the bed has been designed with the patient, caregiver and facility in mind.

# Key Features



## BIO-CONTOUR PROFILING

The patented Bio-Contour profiling system blends a unique combination of bed movements with a curved mattress deck.



## 3 STEP BED EXTENSION

Different bed lengths are now easily configurable in a single sub-frame, offering a simple to use, multi-length hospital bed for greater flexibility and choice.



## UNDERBED LIGHT

The bed exit area on both sides of the bed is illuminated to help guide patients when leaving the bed in a poorly lit room.



## INFECTION CONTROL

The open architecture design allows ease of access to help improve decontamination procedures. Deck sheets are lightweight, smooth and easily removed.



## WEIGH SCALE

The simple to use integrated weigh scale can weigh up to 250 kg (550 lbs). Weighing can be carried out in any position, and items added or taken away using the autocompensation facility without affecting the patient's weight.



## ANTI-ENTRAPMENT SENSORS

The anti-entrapment sensors can detect an object/person underneath the bed. If the beam is interrupted whilst the mattress platform is being lowered, the mattress platform will automatically move up and away from the obstruction, reducing the risk of entrapment.



## PIT STOP MAINTENANCE

Designed for 'Pit Stop Maintenance'- open accessibility means changes such as actuator, control box and battery can be carried out in situ within a few minutes by one person.



## BED EXIT ALARM

When enabled, the bed exit function can detect patient movement at differing sensitivity levels and trigger an audible alarm to alert medical staff.



## CARDIAC CHAIR POSITION

The caregiver can easily adjust the bed into a cardiac chair position with our simple to use control panel.



## LOW HEIGHT

A key advantage in reducing the risk of injury through falls.



## 30 DEGREE BACKREST ANGLE

The backrest will pause when raised or lowered to an angle of 30 degrees, ensuring easy and positive backrest adjustment time after time.



## INDIGO (OPTIONAL)

IndiGo is the powered 5<sup>th</sup> wheel that makes lighter transport available to any caregiver with just a touch - for safety and simplicity. IndiGo is always available and built directly into your Citadel or Enterprise bed.

Optional:  
IndiGo

DIMENSIONS	MEASUREMENT
Overall standard length	2350 mm (HOB), 2300 mm (HOD)
Overall width	1030 mm
Mattress length standard	2020 mm
Mattress width	880 mm
Overall extended length	2470 mm (HOB), 2420 mm (HOD)
Mattress extended length	2140 mm
Overall length short	2240 mm (HOB), 2190 mm (HOD)
Mattress length short	1910 mm
Top height (with 125 mm castors)	760 mm
Low height (with 125 mm castors)	320 mm
Backrest length	850 mm
Seat length	215 mm
Calf length	560 mm
Thigh length	365 mm

## 3 PD 11.

PRODUCT	MEASUREMENT
Safe working load/Maximum patient weight	250 kg (551 ¼ lbs.) / 185 kg ( 407 lbs.)
Head end panel 'off' base configuration	
Safety standard	IEC60601-2-52
ELECTRICAL	DATA
Ingress protection	IPX4
Shock protection	Class 1, Type B
Power in	3 A max. at 230 V a.c. 50/60 Hz
Power in	5.8 A max. 120 V a.c. 60 Hz

Soft drop safety sides are included as standard for smooth release and controlled descent

ANGLES	MEASUREMENT
Head down tilt	12°
Foot down tilt	12°
Backrest angle	62°
Backrest pause	30°
Thigh angle	20°
Calf angle	16°

3 PD 9.

3 PD 6.

3 PD 7.

3 PD 8.

## LEARN MORE ABOUT ENTERPRISE AND INDIGO



Enterprise Range  
Demonstration Video



IndiGo  
Demonstration Video

March 2020. Only Arjo designed parts, which are designed specifically for the purpose, should be used on the equipment and products supplied by Arjo. As our policy is one of continuous development we reserve the right to modify designs and specifications without prior notice. ® and ™ are trademarks belonging to the Arjo group of companies.

© Arjo, 2020

At Arjo, we believe that empowering movement within healthcare environments is essential to quality care. Our products and solutions are designed to promote a safe and dignified experience through patient handling, medical beds, personal hygiene, disinfection, diagnostics, and the prevention of pressure injuries and venous thromboembolism. With over 6000 people worldwide and 60 years caring for patients and healthcare professionals, we are committed to driving healthier outcomes for people facing mobility challenges.

Arjo AB · Hans Michelsengatan 10 · 211 20 Malmö · Sweden · +46 10 335 4500

www.arjo.com



Arjo.A00105.1.0.INT.EN