



Product Service

Attestation of Conformity

No. N8A 122610 0002 Rev. 00

Holder of Attestation: **Shinson Technology Co.,Ltd**

Block#201, No.9 Chuangye Road
213000 Changzhou, Jiangsu
PEOPLE'S REPUBLIC OF CHINA

Product:

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules
Mono-Crystalline Silicon Photovoltaic Module

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.:

704062378401-00

Date, 2023-09-06



Page 1 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



TUV®



Product Service

Attestation of Conformity

No. N8A 122610 0002 Rev. 00

Model(s):

SxxxM72P3BF (xxx=525-560 in step of 5W)
 SxxxM50P4BF (xxx=480-510 in step of 5W)
 SxxxM66P4BF (xxx=635-675 in step of 5W)
 SxxxM60P4BF (xxx=580-615 in step of 5W)
 SxxxM60P3BF (xxx=465-480 in step of 5W)
 SxxxM72P3 (xxx=530-550 in step of 5W)
 SxxxM54P3 (xxx=400-410 in step of 5W)
 SxxxM10C (xxx=355-365 in step of 5W)
 SxxxM60P2B (xxx=360-380 in step of 5W)
 SxxxM66P4BF (xxx=675-700 in step of 5W)
 SxxxM60P4BF (xxx=615-635 in step of 5W)
 SxxxT54P3BF (xxx=415-445 in step of 5W)
 SxxxT66P4BF (xxx=675-715 in step of 5W)
 SxxxN60BPV (xxx=460-480 in step of 5W)

Black series:

SxxxN48BPV (xxx=355-365 in step of 5W)
 SxxxM54P3BF (xxx=395-415 in step of 5W)
 SxxxM54NF3BFB (xxx=415-445 in step of 5W)
 SxxxM66NT4BF (xxx=675-715 in step of 5W)
 SxxxM60NT3B (xxx=460-480 in step of 5W)
 SxxxM54P3BFB (xxx=415-435 in step of 5W)
 xxx is standing for rated output power at STC

Parameters:

Safety Class:	Class II
Max. System Voltage:	1500V DC
Construction:	Framed, double glass, with Junction box, cable and connector.
Fire Safety Class	Class C according to UL790

Tested according to:

EN IEC 61730-1:2018
 EN IEC 61730-1:2018/AC:2018-06
 EN IEC 61730-2:2018
 EN IEC 61730-2:2018/AC:2018-06

Page 2 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



TUV®