

Link™
THREE WAY STOP COCK
 STERILE, NON-TOXIC, NON-PYROGENIC

Caution :
 For Single use only.
 Not to be used with lipids.

EC REP
 CMC Medical Devices & Drugs S.L.
 C/ Horacio Lengo, N-18, CP 29006,
 Málaga-Spain
 E-mail : info@cmcmedicaldevices.com

CE
 2460

STERILE UNLESS PACKAGE IS DAMAGED

Mfg. Lic. No.: MFG/MD/2019/000081

 8 903172 001627

REF : IT0301-2
LOT : 2206080
 : 2022-06
 : 2027-05

"Sample Not For Sale"

STERILE EO              

Open

THREE WAY STOP COCK
STERILE, NON-TOXIC, NON-FLAMMABLE

Caution:
For single use only.
Not to be used in blood

Lot
CQC Medical Devices & Equipment Ltd
Chesham Road, R-12, Chesham
Bucks, Bucks
Tel: 0494 470000

STERILE UNLESS OPENED

Mfg. Lot: MFG/100

REF : 1100

LOT : 2200

Weight: 10g

STORING IN COOL & DRY PLACE

La-med
1382A, Pindar Road, 131000

Customer Care No: 01-1111111

10/2000/12/1000/1000

Range of 3 Way Stop Cock with & without Extension

LinkTM 3 - Trijų krypčių kraneliai - Three Way Stopcock (Standard)

Provides multiple access ports during infusion and transfusion for standard non lipid IV fluids and other solutions. Also can be used during IBP monitoring. gerai prisijungiantys prie kateterio.

Blue coloured standard tap.

LinkTM 3LR - Three Way Stopcock (LR)

Provides multiple access ports during infusion and transfusion for lipid containing IV fluids and other solutions.

LinkTM 3CLR - With click feel at every 45°

The new generation stop cock with click feel at every 45° rotation for correct feel of movement (TYVEK PACKED).

Features & Benefits :

- 360° tap rotation.
- Red and blue pegs/stubs for arterial and venous line identification.
- Pressure tested to 5 bars.
- Minimum priming volume & low dead space.
- Polycarbonate material.

LinkTM 3XT - Three Way Stopcock with Ext. Tube

Provides extended IV fluid pathway alongwith multiple access port during transfusion and infusion.

Features and Benefits :

- Stopcock at one end and MLL luer connector at another end.
- Rotation allowed for 360°.
- Red and blue pegs/stubs for arterial and venous line identification.
- Pressure tested pneumatically and hydrostatically for up to 5 bars.
- Minimum priming volume.
- Tube Length 5 - 250 cms.

Options Available

- DEHP free tube, Combi lock.

Single use | Sterile | Non Pyrogenic



Specifications

Ref/Art No. Std	Ref/Art No. Lipid	Ref/Art No. Click type LR	Colour Code	Packing Inner/Outer unit
IT0301-1	IT0302-1	IT0303-1	Red	50/1000
IT0301-2	IT0302-2	IT0303-2	Blue	50/1000
IT0301-3	IT0302-3	IT0303-3	White	50/1000



Specifications

Ref/Art No.	Length	Packing Inner/Outer unit
IT0701-10	10 cm	50/1000
IT0701-25	25 cm	50/1000?
IT0701-50	50 cm	50/1000
IT0701-100	100 cm	50/1000
IT0701-150	150 cm	50/1000
IT0701-200	200 cm	50/1000