

Welcome to Giorgio Bormac S.r.l.



Cerca (per parola chiave o codi



HOME PAGE

COMPANY

PRODUCTS

DOWNLOAD

SUPPORTO

CONTACTS



Your account





Waterbath ARGOLAB WB 5 Lt

Features

Working range: +5°C RT ... +85 / +100 °C

Volume 5 / 12 / 22 / 40 l

Backlit LED display

Other features

Waterbath Argolab.

Safety class 2 (DIN 12880).

7. Aliarmai

Visual and acoustic alarms which can be silenced by the operator.

Digital timer with a range of programming 1

min - 99 h 59 min and continuous working.

6. Laikmatis

Possibility to set a delayed start of heating cycle.

"Safe temperature" function: working temperature limiter for sample protection.

Internal tank and drilled bottom plate (removable) in high quality stainless steel.

WB 22 Pump and WB 40 Pump ensure a faster and more uniform temperature distribution thanks to the recirculation pump.

Power supply: 220 ± 10% V - 50/60 Hz.

Supplied as standard

9. Dangtis komplektacijoje

stainless steel lid with 5 mm hole for the passage of an external probe, drilled bottom plate and a pipe for the drainage of the tank and quick-acting valve for periodic fluid replacement.

Specifiche Tecniche **Area Download** Informazioni

| Caratteristiche | | |
|--------------------------|--------------------|----------------------------------|
| Capacity | 5 | 1. Talpa - 5 L |
| Min. height (lid closed) | 150 | 2. Minimalus gylis/aukštis 15 cm |
| Security class | 2 | |
| Dimension | 480 x 215 x 335 | |
| Frequency | 50 - 60 | |
| Warranty | 2 | |
| Working method | natural convection | |
| Weight | 8 | |



| Caratteristiche | |
|--------------------------------|-----------------|
| Recirculation pump | No |
| Pump flow rate max. | |
| Absorbed power | 700 |
| Tub width | 150 |
| Temperature resolution | 0,1 |
| Timer | 99 : 59 |
| Temperature variation at 37 °C | ±0,1 |
| Useful volume | 5 |
| Power supply | 230 |
| Internal dimensions | 300 x 155 x 150 |
| Dimension (plate) | 270 x 120 |
| Overtemperature security | Electronic |
| Working temperature | +5 Ta...100 |
| Display | LCD |



| Caratteristiche | |
|-------------------------------------|--|
| Regulations | 2006/95/EC - 2004/108/EC - EN61326-1:2006 - EN6101G-1:2010 - EN61010-2-010:2003 |
| Temperature homogeneity at 37 °C | ±0,2 |
| Resolution | 0,1 |
| Packaging dimensions (W x D x H) | 550 x 300 x 400 |
| Rack capacity | 2 slot |
| Supplied as standard | |

Altri prodotti in questa categoria



**Waterbath ARGOLAB WB 5 Lt**

: 41101592

**WATERBATH ARGOLAB WB 12 Lt**

: 41101602

**WATERBATH ARGOLAB WB 22 Lt (with pu...**

: 41101612

GIORGIO 3 BORMAC

Design, manufacture, marketing
and service on scientific
instrumentation and equipment
for laboratory and industry.

Links:

Azienda
Company
History
Etichettatura ambientale
imballaggi spedizioni
progetti

Legal:

P.I. 04168650366
© 2025 Giorgio Bormac
S.r.l.
Privacy Policy
Cookie Policy

Contacts:**Giorgio
Bormac S.r.l.**

Via della Meccanica, 25
41012 Carpi (MO)
Italia





Sostenibilità

Ambiente

Comunità

Collaboratori

Certificazioni qualità

Lavora con noi

SDS

+39 059 653274

info@giorgiobormac.com

made with by tecntrade

