



Technical Data

Tornado LED	Tornado LK	Tornado ^s LK	Tornado ^s LED
Power (W)		27*	
Spray outlet		4 asymmetrical mixed	
Noise level (dBa)		55	
Head diameter (mm)		12,2	
Head size (mm)		13,1 mm (21,3 mm with a 19 mm bur)	
Rotation speed (rpm)		410'000	
Light		LED	
Light intensity (klux)		Approx. 21	
Ceramic ball bearings		Yes	
Weight (g)		60	
Coupling		Unifix	
Warranty		2 years	
Reference		Tornado LED 1600908-001	

* Multiflex® is a registered trademark of KaVo Dental GmbH, Germany

*23 Watt (Tornado) / 20 Watt (Tornado^s) according to new ISO 14457:2017 standard.
Tornado / Tornado^s turbines are able to apply a transitory power at the bur of 30 W / 24 W (during at least 1000 rounds), when the bur encounters an obstacle.



Bien-Air Medical Technologies develops, manufactures, and markets instrumentation devices and systems across multiple dental and surgery specialities. The company operates eight subsidiaries from its Bienne, Switzerland headquarters and is backed by a solid network ...

Information

[Where to buy?](#)

[Where to repair?](#)

[Maintenance of the products](#)

[Privacy](#)

[General Terms and Conditions](#)

[Certificates of Quality](#)

[Careers](#)

Newsletter

Keep up on our always evolving product features and technology. Enter your e-mail and subscribe to our newsletter.

Email Address