

Product Specifications

DT4x/DT2x Desktop Printer

KOPIJA TIKRA

Barcodes Made Easy

Model	DT2x	DT4x
Print Method	Direct Thermal	
Resolution	203 dpi (8 dot/mm)	
Print Speed	7IPS (177 mm/s)	7 IPS (177 mm/s)
Print Width	2.12" (54 mm)	4.25" (108 mm)
Print Length	Min. 0.16" (4 mm)**; Max. 68" (1727 mm)	
Memory	Flash	4 MB Flash (2 MB for user storage)
	SDRAM	16 MB
Sensor Type	Fixed transmissive sensor, central aligned	
	Adjustable reflective sensor	
Media	Types	Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming
	Width	0.6" (15 mm) Min. - 2.36" (60 mm) Max.
	Thickness	0.003" (0.06 mm) Min. - 0.008" (0.2 mm) Max.
	Label Roll Diameter	Max. 5" (127 mm)
	Core Diameter	1", 1.5" (25.4 mm, 38.1 mm)
Printer Language	EZPL, GEPL, GZPL auto switch	
Software	Label Design Software	QLabel-IV / GoLabel (for EZPL only)
	Driver	Windows 2000, XP, Vista, 8, Windows Server 2003 & 2008
	DLL	Windows 2000, XP and Vista
Resident Fonts	Bitmap Fonts	6, 8, 10, 12, 14, 18, 24, 30, 16x26 and OCR A&B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions
	Scalable Fonts	90°, 180°, 270° rotatable
	Download Fonts	Bitmap Fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Asian Fonts 90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions Scalable Fonts 90°, 180°, 270° rotatable
Barcodes	1-D Bar Codes	Code 39, Code 93, EAN 8 /13 (add on 2 & 5), UPC A/E (add on 2 & 5), 12 of 5 & 12 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subset A, B, C), EAN 128, RPS 128, UCC 128, UCC/EAN-128 K-Mart, Random Weight, Post NET, IIF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar
	2-D Bar Codes	PDF417, Datamatrix code, MaxiCode, QR code, Micro PDF417, Micro QR code, Aztec code
Code Pages	Codepage 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 Windows 1250, 1251, 1252, 1253, 1254, 1255, 1257 Unicode (UTF8, UTF16)	
Graphics	Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software	
Interfaces	Serial port: RS-232(DB-9)	
	USB port	
	IEEE 802.3 10/100 Base-Tx Ethernet port (RJ-45)	
Control Panel	One Tri-color LED: Power (Green, Orange and Red) Function Key: FEED	
Power	Auto Switching 100-240VAC, 50-60Hz	
Real Time Clock	Standard	
Environment	Operation Temperature	41°F to 104°F (5°C to 40°C)
	Storage Temperature	-4°F to 122°F (-20°C to 50°C)
Humidity	Operation	30-85%, non-condensing
	Storage	10-90%, non-condensing
Agency Approvals	CE (EMC), FCC Class A, CB, cUL, CCC	
Dimension	Length	8.58" (218 mm)
	Height	6.77" (172 mm)
	Width	3.94" (100 mm)
Weight	2.65 lbs (1.2 Kg), excluding consumables	3.3 lbs(1.5 Kg), excluding consumables
Options & Accessories	Cutter Module	
	Label Dispenser	
	External label roll holder for 10" (250 mm) O.D. label rolls External label rewinder	

* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.

** Minimum print height and maximum print speed specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc. Godex is pleased to test non-standard materials for minimum print height and maximum print speed capability.



Re 2.3 2013/8/1

2016-05-20