

Access Needles

Stainless steel puncture needle with stylet, PTFE coated puncture needle with stylet

- Stainless steel puncture needle extra thin wall for maximum internal diameter.
- PTFE coating provides easy visualization during ultrasound guided needle insertion.

Stainless Steel Puncture Needle with Stylet *Box of 10*

5009 22 020	22G (0.7 mm) x 20 cm, accepts guidewire .021" (0.53 mm)
5009 22 025	22G (0.7 mm) x 25 cm, accepts guidewire .021" (0.53 mm)
5009 21 015	21G (0.8 mm) x 15 cm, accepts guidewire .018" (0.46 mm)
5009 20 015	20G (0.9 mm) x 15 cm, accepts guidewire .021" (0.53 mm)
5009 20 020	20G (0.9 mm) x 20 cm, accepts guidewire .021" (0.53 mm)
5009 18 015	18G (1.2 mm) x 15 cm, accepts guidewire .038" (0.97 mm)
5009 18 020	18G (1.2 mm) x 20 cm, accepts guidewire .038" (0.97 mm)
5009 18 033	18G (1.2 mm) x 33 cm, accepts guidewire .038" (0.97 mm)

97.5.

18G, ilgis 20 cm.
Padengta teflonu.
Su stiletu.
Echogeniška.

PTFE Coated Puncture Needle

Box of 10

5015 18 015	18G (1.2 mm) x 15 cm, accepts guidewire .038" (0.97 mm)
5015 18 020	18G (1.2 mm) x 20 cm, accepts guidewire .038" (0.97 mm)

Trocar Needle

Box of 10

5007 21 015	21G (1.2 mm) x 15 cm, accepts guidewire .018" (0.46 mm)
5007 18 015	18G (1.2 mm) x 15 cm, accepts guidewire .035" (0.89 mm)
5007 18 020	18G (1.2 mm) x 20 cm, accepts guidewire .035" (0.89 mm)

5007

5015

5009



Introducer Sheaths/Needles

Introducer Sheath/Needles

- Transparent or radiopaque sheaths for guidewire insertion or fluid aspiration.

Introducer Sheath Needle

Box of 10

ISN 1915	19G (1.0 mm) x 15 cm with 5F sheath, accepts guidewire .038" (0.97 mm)
ISN 1920	19G (1.0 mm) x 20 cm with 5F sheath, accepts guidewire .038" (0.97 mm)

ISN 1915

