



SECTION 1 - COMPLETE VEHICLE

EU CERTIFICATE OF CONFORMITY
167/2013*2019/519

The undersigned, Marc Larouche, hereby certifies that the following complete vehicle:

- 1.1 Make: BRP
- 1.2 Type: R, 1.2.1 Variant: P, 1.2.2 Version: R
- 1.2.3 Commercial name: Can-Am
- 1.3 Category, subcategory and sub-subcategory of vehicle: T2b
- 1.4 Company name and address of manufacturer:
Bombardier Recreational Products Inc.
565 de la Montagne, Valcourt, Qc, Canada, J0E 2L0
- 1.4.2 Name and address of manufacturer's authorised representative (if any): BRP Europe N.V.,
Skaldenstraat 125, Gent, 9042, Belgium
- 1.5.1 Location of the manufacturer's statutory plate(s): Under driver seat
- 1.5.2 Method of attachment of the manufacturer's statutory plate(s): Glued
- 1.6.1 Location of the vehicle identification number: Front of the vehicle on the right side
- 2 Vehicle identification number: 3JBRRAP52NJ000191
conforms in all respects to the type described in
EU type-approval e13*167/2013*00114*04
issued on 2021/05/26 and can be permanently registered in Member States having
Both Right and Left -hand traffic and using Metric and Imperial units for the
speedometer.

Valcourt, QC, Canada _____
Place Date (yr/month/day) _____
2022/03/08

Title
Director, Product Compliance

SECTION 2

General construction characteristics

- 3.3.1 Number of axles: 3 and wheels: 6
 - 3.3.2 Number and position of axles with twinned wheels: =
 - 3.3.3 Number and position of steered axles: 1; F
 - 3.3.4 Number and position of powered axles: 3; F&R
 - 3.3.5 Number and position of braked axles: 3; F&R
- Constructions characteristics for special purposes*
- 59 Vehicle with machinery mounted on it: Yes
 - 59.1 Description of the machinery and its interaction with the vehicle: Electric winch
- Masses and dimensions*
- 4.1.1.1 Unladen mass(es) in running order: 4.1.1.1.1 max: 650 kg, 4.1.1.1.2 min: 630 kg
 - 4.1.2.1 Technically permissible maximum laden mass(es): 1046 kg
 - 4.1.2.1.1 Technically permissible maximum mass(es) per axle:
Axle 1: 290 kg, Axle 2: 367 kg, Axle 3: 389 kg
 - 4.1.2.2 Mass(es) and tyre(s):

Axle No	Tyre dimension	Rolling Radius (mm)	Tyre Load rating per tyre (kg)	Maximum permissible mass per axle (kg) (*)	Maximum permissible mass(kg)	Maximum permissible vertical load on the coupling point (kg)	Track width (mm)	
							Minimum	Maximum
1	<u>205/85R12 MSI (46F)</u>	<u>330</u>	<u>180</u>	<u>360</u>			<u>1016</u>	<u>1016</u>
2	<u>255/70R12 MSI (52F)</u>	<u>338</u>	<u>215</u>	<u>430</u>	<u>1220</u>		<u>966</u>	<u>966</u>
3	<u>255/70R12 MSI (52F)</u>	<u>338</u>	<u>215</u>	<u>430</u>			<u>966</u>	<u>966</u>
2	<u>205/80-12 MSI (51E)</u>	<u>331.5</u>	<u>195</u>	<u>390</u>			<u>1016</u>	<u>1016</u>
2	<u>255/70-12 MSI (58E)</u>	<u>340.5</u>	<u>236</u>	<u>472</u>	<u>1334</u>		<u>966</u>	<u>966</u>
3	<u>255/70-12 MSI (58E)</u>	<u>340.5</u>	<u>236</u>	<u>472</u>			<u>966</u>	<u>966</u>
3	<u>205/65R12 (46F)</u>	<u>330</u>	<u>180</u>	<u>360</u>			<u>1016</u>	<u>1016</u>
2	<u>255/70R12 MSI (58J)</u>	<u>339</u>	<u>236</u>	<u>472</u>	<u>1304</u>	<u>68</u>	<u>966</u>	<u>966</u>
3	<u>255/70R12 MSI (58J)</u>	<u>339</u>	<u>236</u>	<u>472</u>			<u>966</u>	<u>966</u>
4	<u>205/90-12 MSI (49M)</u>	<u>338</u>	<u>185</u>	<u>370</u>			<u>1016</u>	<u>1016</u>
2	<u>255/70-12 MSI (56M)</u>	<u>349.5</u>	<u>224</u>	<u>448</u>	<u>1266</u>		<u>966</u>	<u>966</u>
3	<u>255/70-12 MSI (56M)</u>	<u>349.5</u>	<u>224</u>	<u>448</u>			<u>966</u>	<u>966</u>
5								
2								
3								

(*) According to the tyre specification.

**Tyre combination #4 is factory installed.