

AVer CAM520 Pro3 tender specification



* Special features are marked in blue.

* Specifications may vary depending on countries and are subject to change without notice.

Camera features:

1. Use Sony **super-low-light 8Mega pixel sensor**, clear and natural imaging in low-light conditions, providing ultra FHD image quality
2. Support Field of view(D/H/V): 84°/ 76°/ 47°
3. Support lens focal length: 3.9 mm (wide) ~ 46.8 mm (tele)
4. Support Lens F#: 1.6 (wide) ~ 2.8 (tele)
5. Support **Smart Frame for automatic FOV adjustment to fit all participants**.
6. Support **Smart Composition for great visibility for individual participant in the meeting room, automatically frame and divide participants* to individual grids without applying software. (*up to 6 participants divided in the frame)**
7. Support Innovative **Preset Framing** to follow presenter based on preset areas.
8. Support WDR (Superb backlight compensation technology for optimizing light balance in high-contrast conditions)
9. Support **36X* total zoom** (12X optical zoom)
10. Support Pan: ±170°. Tilt: +90° (up) -30° (down)
11. Support **Image Mirror, Flip, White Balance (auto/manual/ATW override via AVer PTZ App2)**
12. Support minimum focus distance is 1m.
13. Support **10 camera presets** (through remote control); 128 presets via VISCA
14. Support **People-counting API** for enterprises and third-party software providers can obtain people-counting data for better understanding of meeting-space usage.
15. Support standard tripod screw holes and Kensington slot.
16. Support **3-way (USB, HDMI, IP) streaming** concurrently
17. Support **Audio tracking for Integration with 3rd party ceiling microphone (Shure/Sennheiser/Yamaha/Nuvera) via AVer Preset Link function****

*Please use PTZApp 2 to set up 36X zoom.

**Please download PTZApp 2 to set up Smart gallery, virtual streaming and Preset Link



AVer CAM520 Pro3 tender specification

functionality. For smart gallery and IP virtual streaming, it is required to keep running PTZApp2 on the computer.

Video features:

1. Support video compression format of [H.264](#), [H.265](#), [YUV](#), [MJPEG](#)
2. Support network video compression format of [H.264](#), [H.265](#)
3. Support the below resolution: [\(16:9\) 1920 x 1080, 1280 x 720 at 60, 30, 15fps; 1600 x 900, 960 x 540, 848 x 480, 800 x 448, 640 x 360, 424 x 240, 320 x 180 at 30, 15fps; \(4:3\) 1280 x 960, 800 x 600, 640 x 480, 480 x 360, 320 x 240 at 30,15fps](#)
4. Support IP streaming resolution (Not for USB video stream): 1080p, 720p, 480p and 360p.
5. Support bit rate: 512Kbps, 1Mbps, 2Mbps, 4Mbps, 8Mbps, 16Mbps and 32Mbps.

Network features:

1. Support the network protocol: [RTSP](#), [RTMP](#)
2. Support 10/100/1000 Mbps. (LAN, RJ45 interface)
3. Support [VISCA over IP](#).
4. Support [remote management via AVer EZ Manager 2 software](#).
5. Support [real-time streaming via AVer EZ Live software](#).
6. Support [DHCP / Static IP address setting](#).
7. Support [NTP Server](#).

Security:

1. Support [password protection](#).
2. Support [SSL certificate import](#).

General features:

1. Support [IR remote control](#).
2. Support 3rd party integration: [VISCA](#), [Pelco-P](#), [Pelco-D](#) via RS232 (128 preset points via [VISCA command](#))
3. Support [VISCA over IP](#).
4. Support standard [UVC plug-and-play](#).
5. Support [Web UI management browser IP access via Chrome](#) (Does not support Internet Explorer).
6. Support basic camera settings adjustment via [AVer PTZApp2](#).
7. Support camera wall-mount bracket method.
8. Support TV mount method. (Optional)
9. Support ceiling mount method. (Optional)

AVer CAM520 Pro3 tender specification

10. Support [remote management via AVer EZ Manager 2 software](#).
11. Support [real-time streaming via AVer EZ Live software](#).
12. Support [Virtual Streaming via PTZApp2](#).

System Requirements: (For PC)

1. Support Windows® 7/ 10/ 11.
2. Windows® 10 Enterprise(IoT)LTSC(version 1809)
3. Support Mac OS X 14.4 or later.
4. Support Google Chromebook 3 version 94.0.4606.114 or later.
5. Support 3.2 GHz Intel® Core™ i5-4460 Processor or higher
6. Support 8 GB RAM or more (ex: 16 GB RAM)
7. Support USB 3.1 port, backward compatible with USB 2.0 port

System Requirements: (For web management)

1. Support Chrome: version 76.x or above.
2. Support Firefox: version 69 or above.
3. Not support IE browser

Compatible Applications:

Zoom, Microsoft® Teams, Skype, Google Meet, Intel® Unite™, RingCentral, BlueJeans, V-Cube, LiveOn, CyberLink U Meeting®, Adobe® Connect™, Cisco WebEx®, Fuze, GoToMeeting™, Vidyo, vMix, WebRTC, Wirecast, XSplit

Certification:

1. ZOOM certified
2. FCC/ CE/ BSMI/ KC/ VCCI certified

Dimensions:

1. Package dimensions: 256 x 256 x 274 mm
2. Package weight: 3.335 kg/ 7.35 lbs
3. Camera: 182 x 142.7 x 153 mm/ 1.47 kg
4. Remote control: 200 x 50 x 21 mm/ 0.09 kg

Power Supply:

Tender Specifications

AVer CAM520 Pro3 tender specification

1. AC 100V ~ 240V, 50/ 60 Hz
2. Consumption: 12V, 2A

Environment Data:

1. Operation temperature: 0°C ~ 40°C
2. Operation humidity: 20% ~ 80%
3. Storage temperature: -20°C ~ 60°C
4. Storage humidity: 20% ~ 80%

Package Contents:

1. CAM520 Pro3 unit.
2. Remote Control
3. Power adapter
4. Power cord (10 ft/ 3 m)
5. USB 2.0 Type-B to Type-A cable (16.5 ft/ 5 m)
6. QR code card
7. Wall-mount bracket
8. ¼" tripod screw
9. Mini DIN9 to mini DIN8 RS232 adapter

Optional Accessories:

1. Mini DIN8 to D-SUB9 RS232 adapter
2. Foldable TV mount
3. Ceiling Mount
4. USB3.1 type-B to type-A cable 3m
5. USB3.1 fiber extender 10m/ 20m/ 30m
6. 1-port POE+ injector
7. HDMI Cable

Warranty:

1. AVer provide standard 3 years warranty. (Accessories for 1 year warranty.)

Please visit AVer Global Web Site at: <http://www.aver.com/default.aspx>

