

DIGITAL THERMOMETER

KFT-01/KFT-02



-**Model No.:** KFT-01
 -**Display:** LCD,3.5digits, 19mmx7.5mm
 -**Temperature measurement:** thermistor
 -**Apply for:** Oral / Axillary / Rectal

-**40 seconds response**
 -**sound warning when peak temperature is reached**
 -**Fever Alarm**

-**Accuracy:** $\pm 0.1^{\circ}\text{C}$; ($\pm 0.2^{\circ}\text{F}$)
 -**Resolution:** 0.1°C (0.1°F)
 -**Measurement scope:** $32^{\circ}\text{C}\text{--}42.9^{\circ}\text{C}$ ($89.6^{\circ}\text{F}\text{--}109.2^{\circ}\text{F}$)
 Temperature $<32^{\circ}\text{C}$ (89.6°F) display $\text{Lo}^{\circ}\text{C}$ ($\text{Lo}^{\circ}\text{F}$)
 Temperature $>42.9^{\circ}\text{C}$ (109.2°F) display $\text{Hi}^{\circ}\text{C}$ ($\text{Hi}^{\circ}\text{F}$)

-**Memory records:** 1 sets
 -**Low voltage Indication**
 -**Automatically turn-off function (8 min)**

-**Validity:** 3 years, (**Batteries are not included and the product can be used after calibration by a qualified body**)

-**Power source and voltage:** DC 1.5V, LR41 or AG3

-**Battery life:** Approx.1200 times or 2 years

-**Dimension:** $125\text{mm} \times 18\text{mm} \times 9.2\text{mm}$

-**Unit weight:** Approx. 10g including battery

-**Work environment:**

Temperature $10^{\circ}\text{C}\text{--}40^{\circ}\text{C}$; Humidity: 15%RH~85%RH

Atmospheric pressure: 70KPa~106KPa

-**Transport/Storage condition:**

Temperature $-20^{\circ}\text{C}\text{--}60^{\circ}\text{C}$; Humidity: 10%RH~90%RH

Atmospheric pressure: 70KPa~106KPa

-**Model No.:** KFT-02

-**Display:** LCD,3.5digits, 15.6mmx6mm

-**Temperature measurement:** thermistor

-**Apply for:** Oral / Axillary / Rectal

-**40 seconds response**

-**Accuracy:** $\pm 0.1^{\circ}\text{C}$; ($\pm 0.2^{\circ}\text{F}$)

-**Resolution:** 0.1°C (0.1°F)

-**Measurement scope:** $32^{\circ}\text{C}\text{--}42.9^{\circ}\text{C}$ ($89.6^{\circ}\text{F}\text{--}109.2^{\circ}\text{F}$)

Temperature $<32^{\circ}\text{C}$ (89.6°F) display $\text{Lo}^{\circ}\text{C}$ ($\text{Lo}^{\circ}\text{F}$)

Temperature $>42.9^{\circ}\text{C}$ (109.2°F) display $\text{Hi}^{\circ}\text{C}$ ($\text{Hi}^{\circ}\text{F}$)

-**Waterproof level:** IPX7

-**Memory records:** 1 sets

-**Low voltage Indication**

-**Automatically turn-off function (8 min)**

-**Validity:** 3 years

-**Power source and voltage:** DC 1.5V, LR41 or AG3

-**Battery life:** Approx.1500 times or 3 years

-**Dimension:** $119\text{mm} \times 15.6\text{mm} \times 9.3\text{mm}$

-**Unit weight:** Approx. 7g including battery

-**Work environment:**

Temperature $10^{\circ}\text{C}\text{--}40^{\circ}\text{C}$; Humidity: 15%RH~85%RH

Atmospheric pressure: 70KPa~106KPa

-**Transport/Storage condition:**

Temperature $-20^{\circ}\text{C}\text{--}60^{\circ}\text{C}$; Humidity: 10%RH~90%RH

Atmospheric pressure: 70KPa~106KPa



COCET 可事达
KANGFU MEDICAL

06