


TECHICAL DATA

Issued by:

Technical Information:

Sew-On/Hook	Sew-On/Loop
Base Material: [REDACTED]	Base Material: [REDACTED]
Construction: Standart with woven with cold – cut sewing edges.	Construction: [REDACTED]
Width Tolerance: [REDACTED]	Width Tolerance: [REDACTED]
Weight: [REDACTED]	Weight: [REDACTED]
Thickness: [REDACTED]	Thickness: [REDACTED]
Standart Width Available [REDACTED]	Standart Width [REDACTED]
Standart Length: [REDACTED]	Standart Length: [REDACTED]
Colour: Black	Colour: Black
Washing: Wash the hook & Loop in cool /warm water (r [REDACTED])	

Peel Strength ASTM D5170 / EN 12242	Average:
	
After washing at 40°C temperature	[REDACTED]
After 1 opening & closing cycle	[REDACTED]
After 5000 opening & closing cycle	[REDACTED]
After 10000 opening & closing cycle	[REDACTED]

Shear Strength ASTM D5169 / EN 13780	Average:
	
After washing at 40°C temperature	[REDACTED]
After 1 opening & closing cycle	[REDACTED]
After 5000 opening & closing cycle	[REDACTED]
After 10000 opening & closing cycle	[REDACTED]

Colour fastness:

- Colour fastness to washing 40°C
- Colour fastness to dry-wet rubbing
- Colour fastness to wet perspiration
- Colour fastness to light

- ISO 105-C06
- ISO 105-X12
- ISO 105-E04
- ISO 105-B02

Result