



# KONFIDENCIALU

Sew-On Hook & Loop  
SHEET  
Grade A

TECHICAL DATA



Technical Information:

Sew-On/Hook	Sew-On/Loop
Base Material: F [redacted]	Base Material: [redacted]
Construction: Standart with woven with cold - [redacted]	Construction: Standart with woven with cold - [redacted]
Width Tolerance: [redacted]	Width Tolerance: [redacted]
Weight: [redacted]	Weight: [redacted]
Thickness: [redacted]	Thickness: [redacted]
Standart Width Available: [redacted]	Standart Width Available: [redacted]
Standart Length: [redacted]	Standart Length: [redacted]
Colour: Black	Colour: Black
Washing: Wash the hook & Loop in cool /warm water (max 70° for maximum 30 mins)	

Peel Strength ASTM D5170 / EN 12242	Average:
After washing at 40°C temperature	[redacted]
After 1 opening & closing cycle	[redacted]
After 5000 opening & closing cycle	[redacted]
After 10000 opening & closing cycle	[redacted]

Shear Strength ASTM D5169 / EN 13780	Average:
After washing at 40°C temperature	[redacted]
After 1 opening & closing cycle	[redacted]
After 5000 opening & closing cycle	[redacted]
After 10000 opening & closing cycle	[redacted]

Colour fastness:  
Colour fastness to washing 40°C  
Colour fastness to dry-wet rubbing  
Colour fastness to wet perspiration  
Colour fastness to light

ISO 105-C06  
ISO 105-X12  
ISO 105-E04  
ISO 105-B02

Result

