



## Sew-On Hook & Loop Grade A

Technical Information:

Sew-On/Hook	Sew-On/Loop
Base Material: [REDACTED]	Base Material: [REDACTED]
Construction: [REDACTED]	Construction: [REDACTED]
Width Tolerance: [REDACTED]	Width Tolerance [REDACTED]
Weight: [REDACTED]	Weight: [REDACTED]
Thickness: [REDACTED]	Thickness: [REDACTED]
Standard Width Available: [REDACTED]	Standard Width Available [REDACTED]
Standard Length: [REDACTED]	Standard Length: [REDACTED]
Washing: [REDACTED]	

Peel Strength ASTM D5170 / EN 12242	Average:
	
After washing at 40°C temperature	[REDACTED]
After 1 opening & closing cycle	[REDACTED]
After 5000 opening & closing cycle	[REDACTED]
After 10000 opening & closing cycle	[REDACTED]

Shear Strength ASTM D5169 / EN 13780	Average:
	
After washing at 40°C temperature	[REDACTED]
After 1 opening & closing cycle	[REDACTED]
After 5000 opening & closing cycle	[REDACTED]
After 10000 opening & closing cycle	[REDACTED]

Color fastness:  
 Color fastness to washing 40°C      ISO 105-C06  
 Color fastness to dry-wet rubbing      ISO 105-X12  
 Color fastness to wet perspiration      ISO 105-E04