

# Arthrex Reference Chart

For Instability Anchor Drill and Spear

Anchor	Diameter	Anchor Length / Socket Hole Depth	Material	Drill Item Number	Drill Diameter	Usable Spears			
						Fish Mouth Spear	Toothed Spear	Offset Spear	Oblique Spear
	1.6 mm	19 mm / 22 mm	FiberWire® CL – AR-3600 SutureTape – AR-3602	AR-3600D-1 AR-3600ND-1*	1.6 mm				
	1.7 mm	19 mm / 22 mm	FiberWire® CL, double-loaded – AR-3600-2 SutureTape, double-loaded – AR-3602-2 TigerTail® – AR-3603	AR-3600D-3 AR-3600ND-3*	1.7 mm				
	1.8 mm	19 mm / 22 mm	TigerTail®, double-loaded – AR-3603-2	AR-3600D-2 AR-3600ND-2*	1.8 mm				
	1.8 mm	19 mm / 22 mm	Knotless FiberTak® – AR-3638	AR-3600D-2 AR-3600ND-2*	1.8 mm				
	2.4 mm	11.3 mm	PEEK – AR-2922PS	AR-2922D-24-1	2.46 mm				
	2.9 mm	12.5 mm	BioComposite – AR-2923BC PEEK – 2923PS	AR-2923D AR-2923DT	2.9 mm 3 mm				

Inkaro išmatavimai:  
skersmuo 1,8mm, ilgis 19-22 mm  
AR-3636;  
AR-3638

\* The nitinol drills (ND) are flexible and disposable (single-use) for application with curved spears AR-2948CT or AR-2948CT-2 (stronger curvature).