

COMMERCIAL POOLS & SPAS

Disinfection and dechloramination

In 2003, **BIO-UV** developed and patented a special range of products for disinfecting and dechloraminating commercial pools and spas because, in most countries, chlorine remains mandatory as a disinfectant. So far, more than 2,000 commercial pools & spas in Europe have been equipped to the total satisfaction of their users and operators and for a healthier environment.

All ranges are NSF-50 certified and Cryptosporidium evaluated. Testing measures for certification are above the usual required standard in order to deliver an optimal efficiency level of microorganisms' reduction such as bacteria, viruses, Crypto, Giardia, etc. which are not eliminated by chlorine and ozone at usual level.

PRINCIPLE

The sun emits invisible light: ultraviolet light. This natural phenomenon is reproduced inside the reactors in the **BIO-UV** Group's product ranges using powerful lamps, the result of leading-edge technology, that emit UV-C rays. At 254 nanometers, the optimum wavelength for destroying micro-organisms (viruses, bacteria, algae, yeasts, mould...), UV-C rays penetrate to the heart of DNA and disturb the metabolism of cells until they are totally destroyed. All germs are thus desactivated (including **Legionella** and **Cryptosporidium**) and cannot reproduce.

Today most commercial pools or spas are treated using chlorinated products that are good oxidizing agents, but generate by-products such as chloramines. These by-products are irritant, corrosive and smelly. They are harmful to health and responsible for respiratory illnesses in lifeguards, baby swimmers and competitive swimmers. That is why **BIO-UV** has designed ranges of UV reactors suitable for commercial pools and spas in order to reduce or eradicate these side effects.


BENEFITS

- Continuous treatment, immediate disinfection and dechloramination,
- Very effective and safe disinfection thanks to the application of UV-C rays
- Up to 75% reduction in the combined chlorine rate (chloramines) in order to achieve a mean level of 0.2 to 0.3 ppm
- More environmentally friendly
- Improvement of the ambient air quality for bathers and staff to the benefit of their health
- Greater comfort: no smell of chlorine
- Improvement of the bathing quality by a reduction of chlorinated by-products in water and air which are responsible for irritations of the skin, eyes, mucous membranes, etc...
- Up to 60% savings in water renewal
- Optimization of heating and dehumidification costs
- Quick return on investment: 9 to 24 months
- Simple and easy to install
- Simple to maintain
- Corrosion reduction
- Better image for the establishment

TOUCH SCREEN



- Better user interface
- Display of the reactor different parameters
- Optimised power regulation
- Real time datas
- History of the alarms and events
- Upgradeable programme, available in 6 languages



EFFECTIVE DOSE

The reactors in the **BIO-UV** ranges are dimensioned according to the pump flow rate, as it is the combination of the contact time in the reactor and the power of the lamp(s) that will ensure that the necessary dose (expressed in millijoules per square centimeter or mJ/cm²) sufficient to kill 99.9% of the micro-organisms (bacteria, viruses, algae in suspension,...) is received.

In the specific case of dechloramination, a dose of 60 mJ is essential in order to be able to significantly reduce the chloramines level. The trichloramines are responsible for respiratory irritation and illnesses in staff and bathers.

MP SERIES REACTORS (Medium Pressure lamps)

Description	Max. flow rate in m ³ /h *	Performance in millijoules per cm ² at actual recommended flow rates **	UV Lamp: Number Power consumption	Connection DN	Length of reactor in mm
MPL 030 EL	20	60	1 x 400 W	DN 100	396
	30	60	1 x 600 W	DN 100	396
	50	60	1 x 1 kW	DN 100	396
	80	60	1 x 1,8 kW	DN 125	398
MP 030 EL	30	60	1 x 600 W	DN 80	488
	40	60	1 x 1 kW	DN 80	488
MP 100 TS	80	60	1 x 1 kW	DN 125	1175
MP 125 TS	140	60	1 x 3 kW	DN 150	1152
MP 140 TS	300	60	1 x 3 kW	DN 200	1244
MP 240 TS	450	60	2 x 3 kW	DN 250	1020
MP 340 TS	675	60	3 x 3 kW	DN 300	725
MP 440 TS	900	60	4 x 3 kW	DN 300	824

* Contact us for other flow rates

** The performance of these devices have been calculated at the end of the lamp life and with a transmission of 98%

ADVANTAGES OF THE MP RANGE

- The MPEL range delivers 60 mJ at the end of the lamps' life in order to guarantee optimum dechloramination
- Treatment of high flow rates
- Reactors made from micro-bitted and passivated 316L stainless steel, high resistance to the corrosion
- Hydraulic «in line» inlet/outlet connections with nearly non-existent pressure loss
- High power medium pressure and multiwavelengths lamps for reducing the number of lamps installed
- High frequency electronic ballast
- Manuel quartz sleeve wiper system (automatic system in option)
- UV sensor with PLC for management of efficiency parameters (in option: remote management via a 4-20mA output) providing a continuous measurement of the UV-C radiance intensity and a control of all operation and maintenance parameters
- Temperature sensor within the electrical box and the reactor (in option), flow sensor
- Lamp life: 7,000 to 9,000 hours
- Power regulation: the medium pressure is the only technology which acts on the 3 chloramines (mono-, di- and trichloramines) and which avoids risks of THM's increases.
- MPTS Range: Touch Screen

HO SERIES REACTORS (Very High Output lamps)

Description	Max. flow rate in m ³ /h *	Performance in millijoules per cm ² at actual recommended flow rates **	UV Lamp: Number Power consumption	Inlet/Outlet in mm	Length of reactor in mm	Diameter of reactor in mm
UV 3000 HO	15	60	3 x 87 W	63	1004,6	150
UV 3205 HO	22	60	3 x 87 W	75	1040	205
UV 4205 HO	30	60	4 x 87 W	75	1040	205
UV 5205 HO	37	60	5 x 87 W	75	1040	205
UV 6205 HO	43	60	6 x 87 W	75	1040	205
UV 6273 HO	67	60	6 x 87 W	75	1049	273

* Contact us for other flow rates

** The performance of these devices have been calculated at the end of the lamp life and with a transmission of 98%

ADVANTAGES OF HO RANGE

- The HO range delivers 60 mJ at the end of the lamps life's in order to guarantee optimum dechloramination
- Optimized performance with UV-C lamps using state of the art technology with high-intensity (HO) performance
- Very long lamp life (16,000 hours depending on the number of switchings on)
- Dedicated electronic ballasts guaranteeing maximum UV efficiency of the lamps and integrated control
- Single-base lamps and patented sealing system for an easy maintenance



ZAC de la Petite Camargue • CS90022 • 34403 LUNEL Cedex • FRANCE
Tél : +33(0)4 99 133 911 • Fax : +33(0)4 99 133 919 • email : info@bio-uv.com
www.bio-uv.com



BIO-UV, Technical Partner of the French Swimming Federation

EPA Est. #075659-FRA-001



© 2013 BIO-UV
vL-04/13