

FILTROMAX MANHOLE FILTER AFI PRO 600 S

As odor affects the well-being, ability to focus and even human health, **FILTROMAX manhole filter AFI PRO 600 S** is used in many places where unwanted odors occur.

The **FILTROMAX manhole filter AFI PRO 600 S** insert works reducing and cleaning the odor with a special activated carbon filter material. This prevents the negative impact of the sewage system on the environment and maintains the optimal functioning of the sewer system.

SPECIFICATIONS:

- Manhole filter for absorbing H₂S, SO₂, NH₃, mercaptan gases;
- Working environment temperature from - 20°C to + 50°C;
- Purification efficiency up to 99% H₂S;
- Mounted under the cast iron hatch;
- Mounting types: Assembly anchors stainless steel + polyamide and special assembly handlers made of stainless steel - AISI316;
- Filter housing - HDPE, PE, EPDM, stainless steel;
- Air / gas flow - free, without losses;
- Maintenance and filter replacement - does not require complete disassembly of the device, i. y. the proposed device is such that it can be serviced and the filter charge can be changed without dismantling it;
- Activated carbon - 10 kg, hardness minimum 96%, granules 4 mm, moisture not more than 15%;
- Activated carbon life up to 36 months. Minimum period of operation at least 9 months.

