



OXYMAT A/S

WORLDWIDE MANUFACTURER OF PSA GENERATOR SYSTEMS

Budgetary offer Nr. PC35196

Akvatechna UAB

Rygos. g. 44-50
05272 Vilnius, Lithuania
Tel: +37069881125 Email:
info@akvatechna.lt

Attn: Darius Andriulionis

Valid until:
Salesman:

Nr	Part Nr.	Item	Price	Qty	Discount	Total price
1	O040 ECO	Oxymat Oxygen Generator, O040 ECO				
		Generator Specific.				
		Capacity:	3.2 kg/h			
		Purity:	93% +/-1%			
		Min. inlet pressure:	6 bar(g)			
		Outlet pressure:	4 bar(g)			
		Max. oper. pressure:	10 bar(g)			
		Air consumption:	0.42 m ³ /min FAD			
		Hose connection:	3/4" hose			
		Colour:	RAL7012 Grey			
		Climatic Conditions				
		Ambient temp.:	10°C to 35°C			
		Altitude:	less than 100 meters a.s.l.			
		Compr. Air Spec.				
		Air quality spec.:	ISO 8573.1:2010.2.4.1			
		Dew point:	+3°C			
		Filtration grade:	0.01 micron			
2	DCP1 25001	Display Control 1				
		2 lines text display, numeric keys, Alarm indication				
3	OM1 26101	Oxygen monitor for oxygen generators (standard)				
		Range 0,1-100% Includes alarm function (through control)				

Page 2/7

All deliveries are in accordance with Incoterms 2010 and NL92 (Nordic countries) and Orgalime S2012 (Internationally)		
Terms of payment:	Jyske Bank A/S Vestergade 8-16 DK-8600 Silkeborg	IBAN account no: DK2671360001001887 SWIFT-BIC: JYBADKKK

Denmark: +45 48797811
China: +86 571 86206853

Slovakia: +421 32 7790123
Columbia: +57 1 8126963

www.oxymat.com
sales@oxymat.com