

MULTILATERAL RUNNING ORDER - LEAGUE A, FEED B



UEFA NATIONS LEAGUE 2018
League A, MD XX - Kick-off 20:45 CET
Multilateral Running Order - Feed B



Home Team vs. Away Team					
PRE-MATCH					
Item	Start (CET)	End (CET)	Duration	Description	Graphics
	19:30:00	20:30:00	01:00:00	Pre-Multi Unilaterals	Broadcaster ID ahead of each unilateral
POST-MATCH					
Item	Start	End	Duration	Description	Graphics
	FT+03:00	FT+03:00		FEED A	
POST-MATCH					
Item	Start	End	Duration	Description	Graphics
	FT+03:00	FT+33:00 FT+03:00	30:00 60:00	Post-Multi Flash Interviews Window	End of Post-Multi Flash Interviews Window

Page 1 of 1

3.3 ADDITIONAL HOST BROADCASTER REQUIREMENTS

3.3.1 POWER REQUIREMENTS OVERVIEW

updated

Any mobile unit must be designed, operated and maintained in compliance with IEC 60364-7-717: "Requirements for special installation or locations – Mobile or transportable units" in its latest version.

This international standard describes the accepted approaches for:

- electrical networks inside the truck/unit: TN-S or IT
- protection against electrical shock, double isolation, automatic disconnection
- implementation of RCD protection and/or isolation monitoring
- needs for equipotential measures

Each Broadcaster with the operator of the mobile unit is fully responsible to ensure the compliance with the regulation IEC 60364-7-717.

UEFA reserves the right to do spot checks and to validate the mobile units, and take any appropriate action such as refusing entrance to the UEFA broadcast facilities.

The above regulations are also applicable to the UEFA Nations League Finals and the UEFA Super Cup and the draws, where power is centrally provisioned and monitored by UEFA.

3.3.2 POWER SUPPLY – MULTILATERAL PRODUCTION

updated

It is the responsibility of the host broadcaster to ensure that a fully redundant power supply is available for the multilateral production to guarantee uninterrupted coverage. This includes the provision of a power generator (i.e. ideally a twin pack generator). Fully redundant uninterrupted power should also be provided to the EBU SNG.

Camera 1 plus emergency audio (stereo effects microphone embedded on audio channels 1 and 2 at the camera head) direct Camera Control Unit (CCU) output should be available on a dedicated 30 minutes UPS (Uninterrupted Power Supply). The UEFA SNG supplier to pick up this feed at the HB OB van.

Broadcast partners are reminded that, following European regulations, without RCD protection cannot be operated.

3.3.3 CABLING – MULTILATERAL PRODUCTION

Host broadcasters are responsible for cable installation to all host broadcast positions. Host broadcasters are responsible for delivering/receiving all

multilateral and digital feeds to the demarcation point for handover of the

relevant signals, which is the BNC patch panel located at the HB OB van tailboard

Patvirtinta, Registruota 2020-10-12, 13:42:15 Nr. 18F-1049