

Under no circumstances will other games, practices or activities take place on the same playing court the day of the game.

5.14. Security for IFPCs

The club is responsible for providing adequate security protection for all TV camera crews, radio and TV commentators and their equipment, and for ensuring that no person is allowed to interfere with the actions of any of the TV camera crews or commentators covering the game. This applies to pre-game activities, the game itself and post-game activities, not only in the area where the commentators work, but also in any interview areas. If an IFPC reasonably requests additional security for a broadcast, the home club will be responsible for accommodating said request.

5.15. Venue Access Fees

Access to each game venue, for the IFPC and any rights holder with personalisation facilities, beginning 24 hours prior to each game, will be provided free of charge. There will be no fee or facility charge, whatsoever, for the provision of access for the IFPC as required herein, including any fee for the home club, the home club's arena, the owner or operator of the arena or any other party (if there are any such fees, they must be paid solely by the home club). Moreover, with the exception of the Final Four there will be no fee for power, back-up power, arena lighting, water, use of pre-wired cables or other provisions necessary to ensure a high-quality TV production as provided herein.

5.16. Lighting

For purposes of ensuring a high-quality TV production, all arenas will meet the following lighting requirements. It is understood that adhering to these lighting requirements may be challenging for some clubs and venues. The improvements with the minimum established below are required. After that time, however, the Company will insist that all arenas meet the requirements as a condition of receiving their EuroLeague licence.

All EuroLeague venues must adapt their lighting systems as follows:

Playing Court:

- The horizontal illumination in the playing court area, measured 1m above the floor, will be an average maintained lux level of 2,500. The illumination measured facing the main and reverse angle cameras will be an average maintained lux level of 1,500.