



Product Service

CERTIFICATE

No. Z1A 012795 0178 Rev. 00

Factories: 012795

Model(s): **Waldner - range SCALA**
Storage cupboards
 - Laboratory cabinet
 - Top-mounted cabinet
 - Suspended cabinet
 - Pull-out cabinet
 - Underbench units

Parameters:

Parameters:	All dimensions W x D x H in [mm]:
	Laboratory cabinets: 450/600/900/1200 x 350/550 x 2090 Combinations: rotating massive doors, rotating glass doors, folding doors
	Top-mounted cabinets open and with rotating doors: 450/600/900/1200 x 350/550 x 610/760
	Suspended cabinets: 450/600/900/1200 x 350 x 460/760 Combinations: rotating massive doors, rotating glass doors, sliding glass door, Reinforcement at width of 1200 by a middle bearing max. load capacity: 60 kg
	Pull-out cabinets with 2 or 3 drawers: 600/900 x 550 x 2090 max load per pull-out : 80 kg max. load per tray: 16 kg Hint: Cabinets must be fixed on the wall with at least 2 wall brackets against tilting
	Underbench units: widths: 450/545/600/845/900/1145/1200 depths: 550/650 working heights: 750/900 drawers: 150/200/350/400/600 Load bearing capacity bearing shelf: 30 kg Load bearing capacity drawers: 30 kg Combinations: drawers, rotating doors
	Underbench on plinth: The underbench unit is covered by a working surface. widths: 450/600/900/1200 heights: 720/870 depths: 550/650

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證書 ◆ CERTIFICADO ◆ CERTIFICAT

A4 / 07.17



Product Service

CERTIFICATE

No. Z1A 012795 0178 Rev. 00

	<p>Underbench unit on castors: On rollers, closed underbench unit with double sliding bearing rollers Ø 75mm (two castors without brake rearside; two castors with brake in front)</p> <p>Underbench units with drawers are equipped with an alternating pull-out lock.</p> <p>height: 639/789 depth: 550 width: 450/545/600/845/900/1145/1200</p> <p>Load bearing capacity drawers: 20 kg</p>
	<p>Suspended underbench unit: The closed underbench unit is suspended at the laboratory bench (4 feet / C – foot / Cantilever foot frame) by supporting brackets.</p> <p>widths: 450/545/600/845/900/1145/1200 heights: 379/529 depth: 550 max. load capacity: 90 kg</p>
	<p>Underbench units for fume cupboards: Underbench on plinth: width: 450/545/600/845/900/1145/1200 height: 820 depth: 672</p> <p>Underbench interposed into a steel table frame: width: 450/545/600/845/900/1145/1200</p> <p>heights: 639/716 depth: 550</p>
comment:	<p>All laboratory cabinets and underbench units on socket must be saved against tilting.</p> <p>Rotating doors above the width- / height ration of 600 x 450 fulfill the requirements.</p>

TÜV SÜD
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證書 ◆ CERTIFICADO ◆ CERTIFIKAT ◆ CERTIFICATE ◆ CERTIFICADO ◆ CERTIFICAT

A4 / 07.17

