


Ordering Information

Balloon Diameter (mm)	Balloon Working Length (mm)				
	8	10	12	15	18
1.75	117-1708	117-1710	117-1712	117-1715	117-1718
2.0	117-2008	117-2010	117-2012	117-2015	117-2018
2.25	117-2208	117-2210	117-2212	117-2215	117-2218
2.5	117-2508	117-2510	117-2512	117-2515	117-2518
2.75	117-2708	117-2710	117-2712	117-2715	117-2718
3.0	117-3008	117-3010	117-3012	117-3015	117-3018
3.25	117-3208	117-3210	117-3212	117-3215	117-3218
3.5	117-3508	117-3510	117-3512	117-3515	117-3518
3.75	117-3708	117-3710	117-3712	117-3715	117-3718
4.0	117-4008	117-4010	117-4012	117-4015	117-4018
4.5	117-4508	117-4510	117-4512	117-4515	117-4518
5.0	117-5008	117-5010	117-5012	117-5015	117-5018

Compliance Chart

Pressure atm (kPa)	Balloon Diameter (mm)											
	1.75	2.0	2.25	2.5	2.75	3.0	3.25	3.5	3.75	4.0	4.5	5.0
6 (608)	1.68	1.90	2.14	2.40	2.61	2.86	3.10	3.33	3.54	3.79	4.26	4.70
8 (811)	1.70	1.93	2.17	2.44	2.66	2.91	3.15	3.39	3.61	3.86	4.34	4.80
10 (1013)	1.73	1.97	2.21	2.47	2.70	2.95	3.20	3.44	3.68	3.93	4.42	4.90
NOM* 12 (1216)	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.50	5.00
14 (1419)	1.77	2.03	2.29	2.53	2.80	3.05	3.30	3.56	3.82	4.07	4.58	5.10
16 (1621)	1.80	2.07	2.33	2.56	2.84	3.09	3.35	3.61	3.89	4.14	4.66	5.20
RBP** 18 (1824)	1.82	2.10	2.36	2.60	2.89	3.14	3.40	3.67	3.96	4.21	4.74	5.30
RBP** 20 (2027)	1.84	2.13	2.40	2.63	2.93	3.18	3.45	3.72	4.03	4.27	4.82	5.40
22 (2229)	1.87	2.16	2.44	2.66	2.98	3.23	3.50	3.78	4.10	4.34	4.90	5.49
24 (2432)	1.89	2.20	2.48	2.69	3.02	3.27	3.55	3.83	4.17	4.41	4.98	5.59
26 (2634)	1.92	2.23	2.51	2.72	3.07	3.32	3.59	3.89	4.24	4.48	5.06	5.69

* Nominal Pressure. The nominal in vitro device specifications do not take into account any lesion resistance.
** Rated Burst Pressure. Do not exceed RBP



For more information please visit our website at www.OrbusNeich.com or contact us:

EMEA HEADQUARTERS

Drs. W. van Royenstraat 5
3871 AN Hoevelaken
The Netherlands

Phone +31.33.254.1150
Fax +31.33.254.1151

Toll Free Phone 00800.0254.1150*
Toll Free Fax 00800.0254.1151*

* Only for Belgium, Denmark, France, Germany, Ireland, Netherlands, Norway, Sweden and UK

© 2016 OrbusNeich. All rights reserved. **Not available for sale in the USA.**

#G-70-0283 Rev02

Sapphire and OrbusNeich are registered Trademarks of OrbusNeich Medical, Inc. All data and photos on file. Illustrations are not to be considered as engineering drawings or photos.


True Controlled Compliance and
Ultimate Crossability for a
Wide Spectrum of Vessels




Ultimate Crossability and Tip Entry Profile

Sapphire II NC Coronary Dilatation Catheter is a well-balanced and truly non-compliant balloon catheter engineered to cross tight and calcified lesions.

Crossing Profile Comparison




Enhanced distal Z-Tip with advanced laser welding technology for “ZERO” transition with conventional steerable guidewires



True Controlled Compliance

True non-compliance and minimal **overstretch for reliability** and size accuracy. Sapphire NC **brings** advanced material **engineering for** optimum reliability and deliverability.

Compliance Comparison from Nominal Pressure to RBP



Technical Specifications

Proximal Shaft	2.0F
Distal Shaft	2.36F (1.75 - 2.0 mm); 2.55F (2.25 - 3.5 mm) 2.6F (3.75 - 5.0 mm)
Catheter Working Length	140 cm
Tip Length	1.5 mm tip for ø1.75 mm; 2.0 mm tip for ø2.0 - 3.0 mm 2.5 mm tip for ø3.25 - 5.0 mm
Marker Bands	2
Coating	Hydro-X (distal tip to guidewire exit port); Invio™ (guidewire lumen)
Nominal Pressure	12 atm
Rated Burst Pressure	20 atm (1.75 - 4.0 mm); 18 atm (4.5 - 5.0 mm)