

E-Bar II Printing System

Fast, reliable slide label printing



E-BAR II

Electronic Barcode Printing System

- ✓ Easy-to-use software
- ✓ Simple label and ribbon loading
- ✓ Now enabled for LIS connectivity
- ✓ E-Bar labels are validated for use on all VENTANA systems

General characteristics

- Print up to five lines of customer-defined text and a barcode on each label.
- Printing flexibility allows user to select barcodes or plain text labels for H&E and other applications.
- Specific physicians' panels and custom templates can be developed and saved.
- Labels are heat and chemical resistant.
- Labels have a two-year shelf life.

System includes: catalog number 1632800

- E-Bar II Printer (All required hardware included)
- 1 Print Ribbon* (Prints 8,100 Labels)
- 540 Labels* (1 Roll)
- Full 1-year warranty

** Individual components can be ordered separately*

Electrical characteristics

	US/Japan/Europe
Power supply input voltage	100-120/220-240 VAC ±10%
Power supply output voltage	22.8 VDC/1.8 A
Current	2.2 Amps
Frequency	50/60 Hz
Power connection	Cord suited to country. For US, standard 3-prong grounded.

Physical characteristics

Size (W x D x H)	7.5 in x 12.25 in x 7.83 in (19.1 cm x 31.1 cm x 19.9 cm)
Weight	6.2 lbs (2.8 kg)
Clearances	Clam shell hood requires 12.25 in (31.1 cm) to replace ribbon/label.

www.roche.com
www.ventana.com

© 2013 Ventana Medical Systems, Inc.

VENTANA and the VENTANA logo are trademarks of Roche. All other trademarks are the property of their respective owners.
 N4278 0912B

VENTANA

Empowering | Testing Efficiency