

## 5cm Classic-Softie (19/22)



**Product Code:** 033012

Slip-on for and open cell foam windshield suitable for cylindrical microphones with slots no further than 5cm from the front of the mic and a diameter of 19-22mm.

### Main Benefits:

- Cost effective windshieling which is tough enough to endure ENG and location recording
- World-wide standard for outdoor news broadcast, sports broadcast and on-camera sound
- High-quality windshieling and shockmounting for an affordable price

[Sharing Options](#)[Where to Buy](#)[Description](#)[Tech Specs](#)[Compatibility](#)[Contents](#)[Videos](#)[Resources](#)[FAQs](#)

Suitable for small diaphragm condenser microphones, with slots no further than 5cm from the front of the mic and a diameter of 19-22mm.

To fit microphone diameter: 19-22mm  
Windshield internal Length: 50mm  
Total Windshield Length: 75mm  
Rubber diameter: 70mm  
Overall diameter: 120mm  
Fur length: 25mm  
Fur Colour: Grey  
Height: 70mm  
Net Weight: .04Kg  
Gross Weight: .08Kg

Max Wind-noise Attenuation: 25 dB

Finding the correct slip-on windshield will depend on the type, length and diameter of the microphone. Slip-on windshields are designed for cylindrical shotgun mics, ranging from 19-25 mm in diameter.

For any windshield to work effectively it must cover all the ports on the microphone. Therefore a 12 cm slip-on windshield would be suitable for shotgun microphones, with slots no further than 12 cm from the front of the mic.

The diameter of the microphone is also key, as the fit must be tight in order to achieve a good seal. Rycote slip-on windshields come in two diameter fittings, Standard (19-22 mm) or Large (24-25 mm).

## Product Code(s)



### 5cm Classic-Softie (19/22)

Slip-on for and open cell foam windshield suitable for cylindrical microphones with slots no further than 5cm from the front of the mic and a diameter of 19-22mm.

**Product Code:** 033012