

**PHILIPS**

Peripheral Vascular

Intravascular  
ultrasound

6 pirkimo dalis

**See clearly.**  
Treat optimally.



# Diagnose and treat peripheral vascular disease

Assessing and delivering the right therapy at the right time for the right patient is imperative to improving outcomes. Clinicians need technology that's diverse and adaptable in order to deliver with optimal precision and efficacy.

## Intravaskulinio ultragarso (IVUS) kateteriai aortai

Choose your catheter based on imaging diameter and wire compatibility needed.

IVUS allows assessment of the following:

- % Stenosis
- Calcium and thrombus
- Real time vessel diameter and lesion morphology
- Length of stenosis
- Dissection
- Position of wire in true or false lumen
- Location of side branches (without using contrast)
- Venous compression
- Completeness of treatment

**PV .035 OTW (Aortic)**

**PV .014P RX, PV .018 RX, PV .035 OTW (AV access)**

**PV .018 RX (Arterial)**

**PV .035 OTW (Venous)**

**PV .018 OTW (Arterial)**

**PV .014P RX (Arterial)**

## Intravaskulinio ultragarso (IVUS) kateteriai periferinėms kraujagyslėms.

Please note, this diagram is intended to demonstrate the most commonly used IVUS catheters per procedure type.

All Philips PV IVUS catheters is designed for the evaluation of peripheral vasculature.

# A full line of IVUS catheters to help guide your treatment strategies

Our peripheral imaging catheters help assess the location of the disease and lesion morphology, including calcium and thrombus. IVUS can also be used to appropriately size stents and confirm completeness of treatment.



## Visions PV .035 OTW

- Includes centimeter markers
- 0.038" maximum guide wire compatible
- 60 mm max imaging diameter
- 90 cm working length

Tinkantis iki 60 mm diametro kraujagyslėms

## Reconnaissance PV .018 OTW

- 0.014" and 0.018" guide wire compatible
- 20 mm max imaging diameter
- 150 cm working length

## Visions PV .018 RX

- 0.014" and 0.018" guide wire compatible
- 24 mm max imaging diameter
- 135 cm working length

## Visions PV .014P RX

- 0.014" guide wire compatible
- 20 mm max imaging diameter
- 150 cm working length

## Pioneer Plus re-entry


- 0.014" guide wire compatible
- 20 mm max imaging diameter
- 120 cm working length

# Ordering information and technical specifications

## Visions PV .035 OTW

Minimum sheath 8.5 F  
88901

Suderinamas su 8F introduiseriu




Pritaikytas 0,038 colio vielai

Su 25 rentgenokontrastiniais markeriais distaliniam kateterio gale

Įėjimo profilis 8,2 F


## Reconnaissance PV .018 OTW

Minimum sheath 5 F  
018OTW




## Visions PV .018 RX

Minimum sheath 6 F  
86700



## Visions PV .014P RX

Minimum sheath 5 F  
014R



## Pioneer Plus re-entry

Minimum sheath 6 F  
PPLUS120

