

# Monopolar electrodes

Reusable, shaft  $\varnothing$  2.4 mm and shaft  $\varnothing$  4 mm

Spatula electrode, straight, insulated, 2.3 x 19 mm, length 120 mm



No. 21191-155

No. 21191-055



4.3 kVp

max 95 °C



31191-211

max 138 °C

Knife electrode, straight, 2.4 x 12 mm, length 120 mm



No. 21191-110

No. 21191-010



4.3 kVp


max 95 °C



31191-211

max 138 °C

Spatula electrode, straight, 2.4 x 12 mm, length 120 mm



No. 21191-156

No. 21191-056



4.3 kVp

max 95 °C



31191-211

max 138 °C

Spatula electrode, straight, 2.3 x 19 mm, length 180 mm



No. 21191-157

No. 21191-057



4.3 kVp

max 95 °C



31191-211

max 138 °C

Spatula electrode, straight, insulated, 2.3 x 19 mm, length 180 mm



No. 21191-158

No. 21191-058



4.3 kVp

max 95 °C



31191-211

max 138 °C

No.  $\varnothing$  2.4 mm shaft

No.  $\varnothing$  4 mm shaft

# Monopolar electrodes

Reusable, shaft  $\varnothing$  2.4 mm and shaft  $\varnothing$  4 mm

Knife electrode, straight, 3.4 x 18 mm, length 40 mm



No. 21191-172

No. 21191-072

= 5

4.3 kVp

max 95 °C

31191-211

max 138 °C

Knife electrode, straight, 1.5 x 17 mm, length 40 mm



No. 21191-101

No. 21191-001

= 5

4.3 kVp

max 95 °C

31191-211

max 138 °C

Knife electrode, straight, 3.4 x 24 mm, length 45 mm



No. 21191-100

No. 21191-000

= 5

4.3 kVp

max 95 °C

31191-211

max 138 °C

Spatula electrode, straight, 3 x 24 mm, length 45 mm



No. 21191-102

No. 21191-002

= 5

4.3 kVp

max 95 °C

31191-211

max 138 °C

Spatula electrode, straight, 2.3 x 19 mm, length 45 mm



No. 21191-159

No. 21191-059

= 5


4.3 kVp

max 95 °C

31191-211

max 138 °C

Spatula electrode, straight, insulated, 2.3 x 19 mm, length 45 mm



No. 21191-161

No. 21191-061

= 5

4.3 kVp

max 95 °C

31191-211

max 138 °C

No.  $\varnothing$  2.4 mm shaft

No.  $\varnothing$  4 mm shaft

4.

# Monopolar electrodes

Reusable, shaft  $\varnothing$  2.4 mm and shaft  $\varnothing$  4 mm

Spatula electrode, straight, insulated, 2.3 x 19 mm, length 120 mm



No. 21191-155

No. 21191-055



4.3 kVp

max 95 °C



31191-211

max 138 °C

Knife electrode, straight, 2.4 x 12 mm, length 120 mm



No. 21191-110

No. 21191-010



4.3 kVp


max 95 °C



31191-211

max 138 °C

Spatula electrode, straight, 2.4 x 12 mm, length 120 mm



No. 21191-156

No. 21191-056



4.3 kVp

max 95 °C



31191-211

max 138 °C

Spatula electrode, straight, 2.3 x 19 mm, length 180 mm



No. 21191-157

No. 21191-057



4.3 kVp

max 95 °C



31191-211

max 138 °C

Spatula electrode, straight, insulated, 2.3 x 19 mm, length 180 mm



No. 21191-158

No. 21191-058



4.3 kVp

max 95 °C



31191-211

max 138 °C

No.  $\varnothing$  2.4 mm shaft

No.  $\varnothing$  4 mm shaft

5.

# Connecting cables

## Connecting cables for return electrodes

Return electrode cable, VIO, ICC, ACC, T-Series, Standard, 4 m

for silicone electrodes



No. 20194-070

☞ = 1

0.5 kVp

max 95 °C

📘 30192-126

max 138 °C

Return electrode cable, VIO, ICC, ACC, T-Series, Standard, 5 m

for silicone electrodes



No. 20194-088

☞ = 1

0.5 kVp

max 95 °C

📘 30192-126

max 138 °C

Return electrode cable, VIO, ICC, ACC, International, 4 m

for silicone electrodes



No. 20194-075

☞ = 1

0.5 kVp

max 95 °C

📘 30192-126

max 138 °C

Return electrode cable, VIO, ICC, ACC, International, 5 m

for silicone electrodes



No. 20194-089

☞ = 1

0.5 kVp

max 95 °C

📘 30192-126

max 138 °C

Return electrode cable, VIO, ICC, ACC, non-Erbe units, International, 4 m

for return electrodes with contact stud



No. 20194-079

☞ = 1

0.5 kVp

max 95 °C

📘 30192-126

max 138 °C

Return electrode cable, VIO, ICC, ACC, non-Erbe units, International, 5 m

for return electrodes with contact stud



No. 20194-086

☞ = 1

0.5 kVp

max 95 °C

📘 30192-126

max 138 °C

6.

6.