

Declaration of performance No 1/05

1. Unique identification code of the product type:

Dry pressed ceramic tiles with water absorption $E \leq 0,5\%$

2. Usage and intended application:

For final finishing of internal and external floors and walls, inside and outside buildings

3. Manufacturer:

Ceramika Tubądzin II Sp. z o.o.

Ul. Armii Krajowej 20

95-035 Ozorków

www.tubadzin.pl

4. System of assessment and verification of constancy of performance of the construction:

Assessment system 4

5. Harmonized standard: EN 14411:2012

6. Declared performance

Essential characteristics	Performance	Technical specification
Reaction to fire	A1/A1 _{FL}	EN 14411:2012
Breaking strength [N]	≥ 1300	
Release of dangerous substances, for: -cadmium [mg/dm ²] -lead [mg/dm ²]	< 0,01 < 0,01	
Binding strength / adhesion [N/mm ²]: - Cement adhesives - Dispersion adhesives - Reactive resin adhesives	$\geq 1,0$ NPD* $\geq 2,0$	
Antislip properties according to standard CET/TS 16165:2012; attachment B	$\leq R13$	
Durability for: - Interior applications - Exterior applications: freeze – thaw resistance (frost resistance)	Compliant Compliant	
Resistance to thermal shock	Compliant	
Touch sensation	NPD*	

*no performance defined

7. Appropriate technical documentation or special technical documentation:

The performance of the above specified product is compliant with the set of declared performance. This declaration of performance has been issued in line with the regulation (UE) no. 305/2011 under the sole responsibility of the above specified manufacturer.

Signature on behalf of the producer:

Karol Chmielewski – Plant Director

Date and place of issue: 15.11.2019, Ozorków