



**REAR
TRACTOR TYRES**

KNK50

- High traction
- Easy movement ability with anti-ground feature
- Preventing clusters in the center and sidewalls during movement
- Facilitating releasing of muds thanks to windowed blocks

Inflated Unloaded Dimensions

Load & Pressure

Product Code	Tyre Size / Ply Rating	TT/TL	Inflated Unloaded Dimensions		Load Index	Speed Index	Load & Pressure			
			Section Width (mm)	Overall Diameter (mm)			Tyre Load Capacity (Kg)	Tyre Pressure At Max. Load (Psi)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)
5323M	420/85-30 8PR	TT	467	1550	139	A6	2430	20	4622	696
5324	18.4-30 10PR	TT	467	1550	145	A6	2900	26	4622	696
5324M	460/85-30 10PR	TT	467	1550	145	A6	2900	26	4622	696
5326	18.4-30 14PR	TT	467	1550	154	A6	3750	40	4622	696
5326M	460/85-30 14PR	TT	467	1550	154	A6	3750	40	4622	696
5413	8.3-32 8PR	TT	211	1195	111	A6	1090	46	3634	559
5423	9.5-32 8PR	TT	241	1250	115	A6	1215	39	3790	581
5433	12.4-32 8PR	TT	315	1360	125	A6	1650	32	4101	625
5514	16.9-34 10PR	TT	429	1585	142	A6	2650	29	4753	720
5514M	420/85-34 10PR	TT	429	1585	142	A6	2650	29	4753	720
5516	16.9-34 14PR	TT	429	1585	148	A6	3150	37	4753	720
5516M	420/85-34 14PR	TT	429	1585	148	A6	3150	37	4753	720
5524	18.4-34 10PR	TT	467	1650	146	A6	3000	26	4937	746
5526	18.4-34 14PR	TT	467	1650	155	A6	3875	40	4937	746
5602	12.4-36 6PR	TT	315	1465	121	A6	1450	24	4429	677
5603	12.4-36 8PR	TT	315	1465	126	A6	1700	29	4429	677
5612	13.6-36 6PR	TT	345	1515	125	A6	1650	23	4571	697
5613	13.6-36 8PR	TT	345	1515	129	A6	1850	29	4571	697
5643	12.4-38 8PR	TT	315	1515	127	A6	1750	29	4587	703
5703	13.6-38 8PR	TT	345	1565	131	A6	1950	29	4728	723
5704	13.6-38 10PR	TT	345	1565	135	A6	2180	33	4728	723
5713	14.00-38 8 PR	TT	345	1565	131	A6	1950	29	4728	723
5714	14.00-38 10PR	TT	345	1565	135	A6	2180	33	4728	723
5724	15.5-38 10PR	TT	394	1570	138	A6	2360	33	4742	725
5524M	460/85-34 10PR	TT	467	1650	146	A6	3000	26	4937	746
5725	15.5-38 12PR	TT	394	1570	141	A6	2575	38	4742	725
5734	16.9-38 10PR	TT	429	1685	145	A6	2900	30	5067	771
5736	16.9-38 14PR	TT	429	1685	152	A6	3550	40	5067	771
5744	18.4-38 10PR	TT	467	1750	147	A6	3075	26	5251	797
5746	18.4-38 14PR	TT	467	1750	154	A6	3750	36	5251	797

KNK50