

FL 09 is a standard low pressure flotation tyre designed with self-cleaning treads for agricultural implements. It is ideal both on road and field use. Its design prevents damage to the field and crops. Its larger footprint spreads the load over a wider area causing soil compaction.



More info [HERE](#)

**SUITABLE FOR**



TYRE SIZE	REC. RO, (INCH)	ALT. RIM (INCH)	UNLOADED DIMENSIONS (MM)				TYPE	PLY RATING	LOAD INDEX & SPEED SYMBOL
			SECTION WIDTH	OVERALL DIAMETER	STATIC LOAD RADIUS	ROLLING CIRCUMFERENCE			
385/65-22.5	AG 11.75	-	423	1042	463	3017	TL	16	154A8   141A8
400/55-22.5	AG 11.75	-	419	1044	452	2993	TL	12	146A8   134A8
400/55-22.5	AG 11.75	-	419	1044	452	2993	TL	16	152A8   140A8
400/60-22.5	AG 11.75	-	410	1045	463	3017	TL	18	158A8   144A8
480/45-17	16	-	470	866	381	2514	TL	-	146A8   134A8
500/45-22.5	AG 16.00	-	503	1015	455	3022	TL	12	149A8   136A8
500/45-22.5	AG 16.00	-	503	1015	455	3022	TL	16	155A8   142A8
500/50-17	16	-	513	915	404	2659	TL	-	149A8-146B   136A8-133B
500/50-17	16	-	513	915	404	2659	TL	-	155A8-151B   142A8-138B
500/55-17	16	-	488	998	445	2911	TL	12	138A8-135B   151A8-148B
500/60-22.5	AG 16.00	-	500	1210	523	3467	TL	12	157A8   145A8