



THERMAL DISINFECTION BY MEANS A BUILT-IN STEAM GENERATOR						
"X"	VOLTAGE	FREQUENCY	RATED POWER	MAXIMUM POWER	ABSORBED CURRENT	FUSES
	200V ~				18 A	20 A
	200V 3~				10 A	
	230V ~	50-60 Hz	4050 W	3200 W	15 A	16 A
	230V 3~				9 A	
	400V 3N~				5 A	

LEGENDA. (Marcare con "X" gli allacciamenti in uso)

X	Pos.	Descrizione
4	A	HOT WATER CONNECTION-3/4"G (TUBE 1/2"G)
	B	COLD WATER CONNECTION-3/4"G (TUBE 1/2"G)
	E1	DRAIN TRAP CONNECTION DN100 (TO WALL)
	E2	DRAIN TRAP CONNECTION DN100 (TO FLOOR)
	F	OMNIPOLAR MAGNETO SWITCH
	G	ELECTRICAL CONNECTION BOX
	H	EQUIPOTENTIAL CLAMP

NOTE:

REFERENCE  
OFFER NR.:

ORD. CONF.  
REFERENCE NR.:

FIRST EMISSION  
DATE: 23/10/2018

OBJECT: **REVO bedpan washer** - DIM.MM. L450x P500x H1500

**Tuttnauer**  
Innovation - Legacy - Partnership

GENERAL TOLLERANCES FOR  
DIMENSIONES AND ELEMENTS  
WITHOUT SPECIFICS TOLLERANCES:  
UNI ISO 2768 - m



PAPER  
SIZE A3  
SCALE 1:10  
PAGE 1 / 1

OP.: C.A.

REV. NR.: DATE

DWG NR.: S-AF2.45SG-01  
(CODE)