



RK710

Upright Cooler GN2/1

Product Features

- Reversible solid door
- Stainless steel cabinet
- Ventilated cooling
- Self-closing door with a 105 degree stop
- Adjustable shelves GN2/1
- Strong wheels
- Lock
- Accessory - Pedal for opening door (right or left hinged)

Measures and Content

| | | |
|--------------------|----|-----------|
| Temperature Range | °C | -2 to +10 |
| Climate Class | | 5 |
| Gross / Net Weight | kg | 148 / 143 |
| Gross / Net Volume | l | 520 / 386 |

Design and Material

| | | |
|---------------------|-------------------|----------------------------------|
| Door No & Type | | 1 hinged self-closing solid door |
| Shelves No & Type | | 3 wire shelves white |
| Shelf Color | | White |
| Shelf Dimensions | | GN2/1 |
| Max load on Shelves | kg/m ² | 110 |
| Castors | | 4 wheels, 2 with brake |
| Exterior Finish | | SS304 |
| Interior Finish | | SS304 |
| Interior Light | | LED |
| Lock | | Yes |

Cooling and Functions

| | | |
|--------------------|---|------------|
| Type of Controller | | Electronic |
| Type of Cooling | | Ventilated |
| Type of Defrost | | Automatic |
| Refrigerant | | R600a |
| Refrigerant Charge | g | 95 |
| Thermometer | | Yes |

Power and Consumption

| | | |
|---------------------|----------|------------|
| Energy Class | | B |
| Energy Consumption | kWh/24h | 1.19 |
| Annual Energy Cons. | kWh/year | 433 |
| Input Power | W | 250 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 48 |

Dimensions

| | | |
|----------------------------|-----|------------------|
| Internal Dimension (WxDxH) | mm | 533 x 700 x 1400 |
| External Dimension (WxDxH) | mm | 740 x 830 x 2010 |
| Packed Dimension (WxDxH) | mm | 770 x 880 x 2070 |
| 40ft Container Load | pcs | 39 |



Adjustable shelves



Digital thermostat