

## SECTION 8 - TECHNICAL DATA

	<b>T45</b>	<b>T47</b>
<b>Material</b>	Aluminium	Aluminium
<b>Weight (without PSU and BLOCK)</b>	2,4Kg	5,2Kg
<b>Overall dimensions (WxDxH)</b>	356 x 282 x 62mm	470 x 460 x 62mm
<b>Warmed surface area (WxD)</b>	356 x 220mm	470 x 400mm
<b>Temperature range</b>	Ambient to 42.0°C	Ambient to 42.0°C
<b>Spot temperature accuracy</b>	±0.2°C	±0.2°C
<b>Temperature set/read</b>	Digital LED display	Digital LED display
<b>Power consumption (Max)</b>	45W*	90W*
<b>Power consumption (Typical*)</b>	30W	50W
<b>Heating</b>	30W*	88W*
<b>PSU</b>	AC input 100-240V 50-60 Hz 1.6A MAX DC output 24V/5A	AC input 100-240V 50-60 Hz 1.6A MAX DC output 24V/5A
<b>Alarms</b>	Audible and visible for out of range temperature	Audible and visible for out of range temperature

8

\*in 23°C ambient and still air, the heated surface has reached 37°C, Power consumption is max during initial warm up phase.