

Technical Datasheet

		EN ISO 13485 certified
Article - No:	04-212-1200	Revision: 5
Remarks	piercable cap	single use only

Specification

5.3

5.1

5.5

5.4

5.2

Product	np Safelock-Cap microcentrifuge tube PP, 1,5ml, attached cap, boil-proof, transparent, grad., writing area, np pcr ready, max. RCF 30.000g, autocl. up to 121°C, CE/IVD
Classification	CE/IVD
Dimensions	outer diameter: 10,80 mm (+/- 0,2 mm) height (without cap): 38,90 mm (+/- 0,2 mm)
Colour	transparent
Graduation	grad., writ. area
Nominal Capacity	1,5ml
Material Characteristics	polypropylene (PP)
Temperature range	-70°C - 75°C in waterbath up to 120 °C
Autoclavability	autocl. up to 121°C
Centrifugation	max. RCF 30.000g
Product Characteristics	biologically inert physiologically harmless constantly usable at temperature of 80 °C up to 100 °C
Purity Grade	free of PCR inhibitors free of human DNA free of RNase and DNase free of pyrogens
Shelf - Life	not limited at controlled storage conditions
Packaging	pcs per bag: 500 pcs per carton: 8.000 pcs per pallet: 160.000
Storage	dry condition: 40%-60% rel. humidity bags / cases orig. closed storage temp. +2°C to max. +30°C

Technical Datasheet

Date: 22.06.20

Page 2 of 2

pal. not stackable

Approved by nerbe plus quality department
--