

Technical Datasheet

Date: 22.06.20

Page 1 of 2

EN ISO 13485 certified

EN ISO 13485 certified		
Article - No:	04-332-1200	Revision: 7
Remarks	piercable cap	single use only
Specification		
6.2 6.1 6.4 6.2 6.1		
Product	np Safelock-Cap microcentrifuge tube PP, 0,5ml, attached cap, boil-proof, transparent, grad., writing area, np pcr ready, max. RCF 30.000g, autocl. up to 121°C, CE/IVD	
Classification	CE/IVD	
Dimensions	outer diameter: 7,70 mm (+/- 0,2 mm)	
	height (without cap): 31,20 mm (+/- 0,2 mm)	
Colour	transparent	
Graduation	grad., writ. area	
Nominal Capacity	0,5ml	
Material Characteristics	polypropylene (PP)	
Temperature range	-70°C - 75°C	
	in waterbath up to 120 °C	
Autoclavability	autocl. up to 121°C	
Centrifugation	max. RCF 30.000g	
Product Characteristics	biologically inert	
	physiologically harmless	
	constantly usable at temperature of 80 °C up to 100 °C	
Purity Grade	free of PCR inhibitors	
	free of human DNA	
	free of RNase and DNase	
	free of pyrogens	
Shelf - Life	not limited at controlled storage conditions	
Packaging	pcs per bag: 500	
	pcs per carton: 10.000	
	pcs per pallet: 240.000	
Storage	dry condition: 40%-60% rel. humidity	
	bags / cases orig. closed	
	storage temp. +2°C to max. +30°C	

Technical Datasheet

Date: 22.06.20

Page 2 of 2

	pal. not stackable
Approved by nerbe plus quality department	