



## DECLARATION OF PERFORMANCE

**Declaration of Performance No:** CPRDoP/ET-001

**1. Identification of product:**

Dry pressed ceramic floor tile,  $0,5\% < Eb \leq 3\%$

**2. Intended use(s):**

For internal and external floorings

**3. Name and contact address of the manufacturer:**

Seramiksan Turguthu Seramik San. Ve Tic. A.Ş.  
Organize Sanayi Bölgesi 45401 Turguthu / Manisa / TURKEY  
Tel: +90 236 313 96 13 Fax: +90 236 313 77 64  
[www.seramiksan.com.tr](http://www.seramiksan.com.tr) [info@seramiksan.com.tr](mailto:info@seramiksan.com.tr)

**4. System or systems of assessment and verification of constancy of performance of the construction product :**

System 4

**5. Declared performance**

Essential characteristics	Performance	Harmonised technical specification	
Reaction to fire	A1fl	EN 14411:2012	
Release of dangerous substance, for	NPD		
- Cadmium			
- Lead			
Breaking strength	Thickness $\geq 7,5$ mm min. S:1100 N Thickness $< 7,5$ mm min. S:700 N		
Slipperiness	Slipperiness value appears on the catalogues and web site		
Facility	NPD		
Bond strength/ adhesion for:	Cementitious adhesive, type C2 Min.1 N/mm <sup>2</sup>		
Thermal shock resistance	Pass		
Durability for:			
- internal use:	Pass		
- external use: frost resistance	Pass		

The performance of the product identified in point 1 is in conformity with the declared performances in point 5

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

**Signed for and on behalf of the manufacturer by:**

Engin AKGÜN

Quality Assurance & Process Control Manager

05.06.2013/Manisa/Turkey