

Connecting cables

Bipolar connecting cables

Bipolar connecting cable, VIO, ICC, ACC, International (2-Pin 22 mm), 4 m

for bipolar scissors BiSect



No. 20196-107



1 kVp

max 95 °C



30192-126

max 138 °C

Bipolar connecting cable, 2-Pin 28 mm, forceps, angled plug, length 4.5 m

for bipolar forceps with european flat plug



No. 20196-064



1 kVp

max 95 °C



30192-126

max 138 °C

Bipolar connecting cable, Valleylab and non-Erbe units (2-Pin 28 mm), 4 m

for bipolar forceps with european flat plug



No. 20196-055



1 kVp

max 95 °C



30192-126

max 138 °C

3.1

Bipolar connecting cable, Valleylab and non-Erbe units (2-Pin 28 mm), 4 m

for bipolar forceps with 2-Pin connection



No. 20196-127



1 kVp

max 95 °C



30192-126

max 138 °C

Bipolar connecting cable for da Vinci, Valleylab and non-Erbe units (2-Pin 28 mm), 4 m

for bipolar forceps with 2-Pin connection



No. 20196-129



1 kVp

max 95 °C




30196-043

max 138 °C

Bipolar connecting cable, 2-Pin 28 mm, fixation forceps, length 4.5 m

for bipolar fixation forceps 20195-080, 20195-081, 20195-086, 20195-092, 20195-093 and bipolar STORZ fixation forceps



No. 20196-067



1 kVp

max 95 °C



30192-126

max 138 °C

Bipolar forceps

Bipolar forceps Classic, straight

Bipolar forceps Classic, angled, tip 2 mm, blunt, length 190 mm



No. 20195-007

☒ = 1

0.5 kVp

max 95 °C

📄 30195-011

max 138 °C

Bipolar forceps Classic, angled, tip 2 mm, blunt, length 190 mm

without guide bar



No. 20195-492

☒ = 1

0.5 kVp

max 95 °C

📄 30195-011

max 138 °C

Bipolar forceps Classic, straight, tip 1 mm, blunt, length 225 mm

without guide bar



No. 20195-041

☒ = 1

0.5 kVp

max 95 °C

📄 30195-011

max 138 °C

3.3

Bipolar forceps Classic, straight, tip 2 mm, blunt, length 225 mm

without guide bar



No. 20195-030

☒ = 1

0.5 kVp

max 95 °C

📄 30195-011

max 138 °C

3.2

Bipolar forceps Classic, short angled, tip 0.7 mm, fine, length 225 mm



No. 20195-064

☒ = 1

0.5 kVp

max 95 °C

📄 30195-011

max 138 °C

Bipolar forceps

Bipolar forceps Classic, straight

Bipolar forceps Classic, straight



No.	
= 1	0.5 kVp
	max 95 °C
30195-011	max 138 °C

Form of tip	Length	Length of tip	Form of forceps	Type of clasps	No.
100 % Tip 0.2 mm, pointed 	105 mm	6 mm	straight	punctiform	20195-019
	105 mm	5 mm	short angled, 45°	punctiform	20195-022
	105 mm	6 mm	angled, 45°	punctiform	20195-023
	165 mm	6 mm	straight	punctiform	20195-011
	165 mm	6 mm	angled, 30°	punctiform	20195-013
	190 mm	6 mm	straight	punctiform	20195-037
Tip 0.3 – 0.4 mm, very fine 	165 mm	6 mm	angled, 30°	punctiform	20195-036
Tip 0.5 – 0.7 mm, fine 	105 mm	6 mm	straight	punctiform	20195-020
	105 mm	6 mm	angled, 45°	punctiform	20195-021
	150 mm	8 mm	straight	punctiform	20195-005
	165 mm	5 mm	short angled, 45°	punctiform	20195-066
	190 mm	5 mm	short angled, 45°	punctiform	20195-065
	225 mm	5 mm	angled, 45°	punctiform	20195-064
Tip 1 mm, blunt 	145 mm	10 mm	straight	punctiform	20195-038
	165 mm	6 mm	straight	punctiform	20195-010
	165 mm	10 mm	straight	punctiform	20195-039
	165 mm	6 mm	angled, 30°	punctiform	20195-014
	165 mm	6 mm	angled, 30°	punctiform	20195-493
	190 mm	10 mm	straight	punctiform	20195-040
	190 mm	8 mm	straight	parallel	20195-000
	190 mm	8 mm	angled, 30°	parallel	20195-001
	190 mm	6 mm	angled, 30°	parallel	20195-490
	225 mm	10 mm	straight	punctiform	20195-041
Tip 2 mm, blunt 	145 mm	10 mm	straight	punctiform	20195-027
	165 mm	10 mm	straight	punctiform	20195-028
	190 mm	10 mm	straight	punctiform	20195-029
	190 mm	6 mm	angled, 30°	punctiform	20195-007
	190 mm	6 mm	angled, 30°	punctiform	20195-492
	225 mm	10 mm	straight	punctiform	20195-030
	260 mm	10 mm	straight	punctiform	20195-110
300 mm	10 mm	straight	punctiform	20195-109	

3.3

3.2

Bipolar connecting cables	Length	Piece	No.
Standard	4 m	1	20196-045
	5 m		20196-057
MF plug	4 m	1	20196-124
International (2-Pin 22 mm)	4 m	1	20196-053
	5 m		20196-061
Martin Standard	4 m	1	20196-047
	5 m		20196-059
Valleylab (2-Pin 28 mm)	4 m	1	20196-055

8.0