

# Specifications

|                          |                |                                    |  |
|--------------------------|----------------|------------------------------------|--|
| <b>CRI</b>               | ≥ 96           | <b>TLCI</b>                        | ≥ 96   |
| <b>CQS</b>               | ≥ 95           | <b>SSI (D56)</b>                   | 74   |
| <b>SSI (Tungsten)</b>    | 85             | <b>Color Temperature</b>           | 2700K~6500K  |
| <b>Radio Frequency</b>   | 2.4GHz         | <b>Power Consumption</b>           | ≤350W  |
| <b>Cooling Method</b>    | Active Cooling | <b>Channels</b>                    | 36925  |
| <b>Remote Ability</b>    | ≤100m          | <b>Groups</b>                      | A/B/C/D  |
| <b>Radio Frequency</b>   | 2.4GHz         | <b>Power Supply</b>                | AC 100 ~ 240V<br>50/60Hz                                 |
| <b>Operating Current</b> | 3.5A           | <b>Operating Voltage (Battery)</b> | ≥ 15A 12V-16.8V  |
| <b>APP Control Type</b>  | Bluetooth      | <b>Control Methods</b>             | 2.4GHz Remote,<br>Bluetooth Sidus Link, 5-<br>pin DMX512 |
| <b>Net Weight</b>        | 7.315kg        | <b>Size (Light)</b>                | 29.84*21.56*34.45cm /<br>11.75*8.49*13.56in              |