



GreenFields Slide Max Elite

40 165 15.6

TECHNICAL DATA

T100193

Type	Synthetic grass carpet for a filled performance system, 5/8" gauge tufted, straight stitch pattern	
Pile content	100% polyethylene monofilament, U.V.- resistant, Diamond shape, 15.600/6 dTex, 410 microns	
Primary backing	Double 100% PP Thiobac, black, U.V.- stabilized, weight ca. 252 gr/m ²	
Secondary backing	Latex compound with a base of styrene-butadiene with drainage holes	
Pile height	40 mm	+/- 5%
Total thickness	42 mm	+/- 5%
Stitch rate per 1m (width)	63	
Stitch rate per 1m (length)	165	+/- 10%
Number of tufts/m ²	10.395	+/- 10%
Number of filaments/m ²	124.740	
Pile weight	1.535 gr/m ²	+/- 10%
Weight primary backing	252 gr/m ²	
Weight secondary backing	1.000 gr/m ²	
Total weight	2.787 gr/m ²	+/- 10%
Roll width	according to seaming plan	+/- 2cm
Roll length	according to seaming plan	
Tuft bind	≥ 40 Newton	
Water permeability	≥ 500mm/h	
Color Fastness	Xenon test : blue-scale>7, grey-scale>4	

Version 1.1, 26/03/2021

COLOUR

Duo tone (Field green/Lime green), White and yellow for line marking.

RECOMMENDED SYSTEM

Carpet needs to be filled with stabilizing and/or performance infill with a max free pile of 18mm
Use of a prefabricated shockpad or insitu layer is strongly recommended
For certified system configurations see page 2 or consult your sales representative

INSTALLATION INSTRUCTION:

This product should be stored, handled and installed in accordance with the installation manual, ask our sales representatives for the latest version.



All data shown are typical values based on tests believed to be reliable by TenCate. All technical data provided herein are subject to change without prior notification. TenCate assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by TenCate. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.



GreenFields Slide Max Elite

40 165 15.6

AVAILABLE SYSTEMS

System name	Performance Infill	Stabilizing Infill	Pad / E-layer / Geo	Tested
GreenFields Slide Max Elite 40 165 15.6 s EPDM-st EL30	EPDM 8mm 5kg/m ²	Sand 14mm 20kg/m ²	EL30	
GreenFields Slide Max Elite 40 165 15.6 s EPDM-st ET35	EPDM 8mm 5kg/m ²	Sand 14mm 20kg/m ²	ET35	
GreenFields Slide Max Elite 40 165 15.6 s nature ET35	Cork 11mm 1,6kg/m ²	Sand 16mm 23kg/m ²	ET35	D
GreenFields Slide Max Elite 40 165 15.6 s sbr EL25	SBR 13mm 7kg/m ²	Sand 12mm 18kg/m ²	EL25	ABD
GreenFields Slide Max Elite 40 165 15.6 s sbr EL30	SBR 13mm 7kg/m ²	Sand 11mm 15kg/m ²	EL30	
GreenFields Slide Max Elite 40 165 15.6 s sbr ET35	SBR 13mm 7kg/m ²	Sand 11mm 15kg/m ²	ET35	
GreenFields Slide Max Elite 40 165 15.6 s sbr PE08.7	SBR 13mm 7kg/m ²	Sand 13mm 18.2kg/m ²	HP XC 070 008	ABD
GreenFields Slide Max Elite 40 165 15.6 s sbr PE10.7	SBR 13mm 7kg/m ²	Sand 13mm 18.2kg/m ²	HP XC 070 010	ABD

Version 1.1, 26/03/2021

SYMBOLS EXPLAINED

- A** FIFA Quality Programme for Football Turf, Handbook of Requirements October 2015 Edition (Quality)
- B** FIFA Quality Programme for Football Turf, Handbook of Requirements October 2015 Edition (Quality Pro)
- C** The International Rugby Board : Regulation 22, standard relating to the use of artificial playing surfaces.
- D** European standard EN 15330-1, Surfaces for sports areas.
- E** The International Hockey Federation (FIH) "Handbook of performance requirements for synthetic turf hockey pitches"

All data shown are typical values based on tests believed to be reliable by TenCate. All technical data provided herein are subject to change without prior notification. TenCate assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by TenCate. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.